

Features and Benefits

Rear Blades

RBT45 Series

Features	Benefits
Warranty	One year parts and labor.
Working widths	96" & 108"
HP Range	70-125 HP
Cat. 2 and 3	Bushing provided to go from Cat. 2 to Cat. 3 enables a wider variety of tractors to be used.
Quick hitch compatible	Compatible with Land Pride Quick hitch for easy attachment and removal. Increases productivity.
Angle up to 45 degrees	Various angles left or right to move the desired amount of material.
Tilt up to 15 degrees	Tilt up to 15 degrees to do various ditching duties.
Offset up to 35"	Offsets left or right to get moldboard beyond tractor tire or up against obstacles.
Formed 19" moldboard with top lip reinforcement	Formed moldboard with 90 degree bent top for additional strength. Tall moldboard allows for a great deal of material to be moved.
4" Solid steel kingpin	4" Solid steel is matched for workloads up to 125 HP.
5/16" Moldboard with 1/4" reinforcement	Heavy-duty moldboard to handle loads from 125 HP tractors.
Reversible cutting edge	Lengthens blade life by being able to turn cutting edge over and use other edge.
Fully welded reinforced main frame	Overall mainframe strength is enhanced due to being fully welded.
Retractable parking stand	Enables one person hook-up and keeps the mainframe off of the ground.
Grease zerks at all pivot points	Helps front pivot shaft maintain bind free movement.
Heavy-duty pivot assembly	1" Plate steel turntable and 3" kingpin handle the high amount of torque that can be transferred to this area.
Skid shoes (optional)	Skid shoes protect moldboard from hitting low-lying obstructions such as manhole covers.
Side plates (optional)	Side plates allow the blade to hold material in to drag from one spot to another.
Cylinder cushion valve (optional)	Cylinder cushion valve protects the cylinders and blade from sudden impacts by allowing hydraulic fluid to escape vs. blowing seals.
Single or dual gauge wheels (optional)	Gauge wheels position the height of the blade to aid in grading.

Designs, specifications, features and information are subject to change without notice.