

## Features and Benefits

### Blades, Rear

#### RBT60 Series

Features	Benefits
<b>Warranty</b>	One year parts and labor.
<b>10 ft. &amp; 12 ft. Working widths</b>	Choice of two sizes to pick from. Both sizes handle large capacities.
<b>High HP Range</b> <b>2-Wheel drive</b> <b>4-Wheel Drive</b>	225 Hp with 10 ft. blade & 175 HP with 12 ft. blade 200 Hp with 10 ft. blade & 160 HP with 12 ft. blade
<b>Cat. II and Cat III 3-Point Hitch</b>	Can go from Cat. II to Cat. III 3-point tractor. Enables a wider variety of tractors to be used.
<b>Quick hitch compatible</b>	Compatible with Land Pride QH20 Cat. II Quick hitch for easy attachment and removal. Increases productivity.
<b>Blade angles up to 45 degrees left or right hydraulically</b>	Allows the operator to set the blade at the angle of his choice to complete the job with satisfactory results.
<b>Blade tilts up to 15 degrees up or down hydraulically</b>	Allows the operator to do simple tasks such as putting a crown in the middle of a road to making V-type ditches of various sizes.
<b>Blade offsets up to 55" left or right hydraulically</b>	Allows the operator to position the end of the moldboard beyond tractor tire and close to solid obstacles such as fences, buildings and abutments.
<b>Formed 19" high moldboard</b>	Can move a great deal of material in a short time.
<b>4 1/2" Diameter solid steel moldboard kingpin</b>	Matched for workloads up to 225 HP 2-wheel or 200 HP 4-wheel drive tractors with 10 ft. moldboard and 175 HP 2-wheel or 160 HP 4-wheel drive tractors with 12 ft. moldboard.
<b>1/2" Formed Moldboard with 3/8" formed channel reinforcement</b>	Makes it one of the strongest moldboards in its class for handling heavy loads.
<b>Mainframe is fully welded and reinforced</b>	Overall Mainframe strength is enhanced due to being fully welded.
<b>Retractable parking stand</b>	Enables one person hook-up and keeps the Mainframe off of the ground.
<b>Front pivot shaft has two grease points</b>	Helps front pivot shaft to move easily.
<b>Heavy-duty blade pivot assembly</b>	1" Plate steel turntable and 4 1/2" kingpin handle tremendous torque delivered by up to 225 HP tractors.
<b>Accessories</b>	
<b>Skid shoes</b>	Skid shoes protect moldboard from hitting low lying obstructions such as manhole covers.
<b>Side plates</b>	Side plates allow the blade to hold material in to drag from one spot to another.
<b>Dual gauge wheels</b>	Gauge wheels position the height of the blade to aid in grading.

*Designs, specifications, features and information are subject to change without notice.*