



Features and Benefits

Drag Scraper

BB4510 & BB4512 Models

| Features | Benefits |
|--|---|
| 70 to 125 HP Range | Fits a wide variety of tractors. |
| 4 x 4 Square tube cross beam | Square tubing is structurally strong. Helps keep the Box Scraper square. |
| 3/8" Heavy side panels with angle reinforcement on the diagonal | Built heavy to handle tough jobs and to keep the side panels straight under side loads. |
| 1/4" Formed moldboard with internal brace bars and 3" x 3" x 3/8" angle reinforcement at the cutting edge | Formed moldboard helps keeps materials flowing, decreases drag, lowers horsepower requirements and speeds up work. Brace bars extending from crossbeams to lower moldboard keep the moldboard straight under heavy loads. Angle reinforcement at the cutting edge helps keep the cutting edge straight. |
| Side Panels have vertical gussets at the front | Vertical gussets help keep the panels straight vertically under side loads. |
| 1/2' x 6" Heat-treated, reversible and replaceable cutting blade | Heat-treated high carbon steel for hardness giving the cutting blade long life. Reversible so both edges can be used before replacing the cutting blades. |
| 24" High Moldboard and side panels | Has a high material capacity for doing a lot of work in a short time. BB4510 = 2 1/4 cu. yd. capacity and BB4512 = 2 3/4 cu. yd. capacity |
| 5" Maximum cutting depth | Can load the bucket quickly. |
| 21" Dump clearance | Capable of dumping a lot of material quickly. |
| Optional tilt with 6 3/16" Drop on the right side blade point | BB4510 with 7 5/8" blade drop and BB4512 with 8 1/4" blade drop. Capable of making deep angle cuts in one pass. |
| Optional weight tray | Weight tray can be filled with 760 lbs. of concrete to help force the cutting blade into the material. |

Designs, specifications, features and information are subject to change without notice.