

**FM21 Series**

Features	Benefits
60" & 72" Cutting widths	Good cutting widths for applications in this HP range.
25-55 HP gearbox rating	Fits a large array of consumer, municipality, and landscape of tractors.
3-Point hitch offsets mower to the right: FM2160 Offsets mower 1/2" or 6 1/2" FM2172 offsets mower 6 1/2" or 17 1/2"	The two position hitch mounting allows the mower to be offset to the right for a closer cut alongside buildings, fences, and roadsides.
One year gearbox warranty	The gearbox is designed tough to withstand the rigors of flail mowing.
3/4" – 4" Cutting height	Variable cutting heights for many uses.
1" Cutting capacity	Can cut small saplings.
Duckfoot style knives	Heavy enough to cut 1" material.
5" Rotor diameter	Large rotor diameter protects against obstructions.
Reverse rotor rotation	Brings the cut material up and over which allows it to be dispersed more evenly.
High knife tip speed	Knife tip speed of 7,385 fpm provides for a clean cut.
Cat. 4 driveline with over-running clutch in gearbox	Upon disengaging the PTO, the over-running clutch allows the driveline to quit turning, while the clutch yoke, gearbox, and rotor shaft slow down under their own inertia.
3 - "B" Section belts	"B" Section belts fit snug in the sheaves, and the multiple belts ensure positive transfer of power.
Baffles on the top inside of the deck	Keeps the cut material from clumping together, ensuring an even distribution of clippings.
Height adjusting roller	Rear height adjusting roller with greaseable bearings and tapered ends to prevent gouging during turns.
Standard scrapers on rear height adjusting roller	Keeps the roller clean for consistent cutting height.
Adjustable rear panel	Adjusts to allow strong discharge of material and aids in cleaning underside of deck.