

Features and Benefits

Flail Mowers

FM20

Features	Benefits
60" & 72" Cutting widths	Good cutting widths for applications in this HP range.
25-55 HP gearbox rating	Fits a large array of consumer, municipality and landscape of tractors.
3-Point hitch can be centered or offset 6 1/4" to the right	The two position hitch allows the mower to be centered behind the tractor or offset 6 1/4" to the left for a closer cut alongside buildings, fences and roadsides.
One year gearbox warranty	The gearbox is designed tough to withstand the rigors of flail mowing.
3/4" – 4" Cutting height	Variable cutting heights for many uses. Lowest cutting height allows for scalping in grasses such as Bermuda prior to overseeding.
1" Cutting capacity	Can cut small saplings.
3 Fine cut knives per hanger	Heavy enough to cut 1" material and cuts fine enough to groom a yard.
4 1/4" Rotor diameter	Large rotor diameter protects against obstructions.
Reverse rotor rotation	Brings the cut material up and over which allows it to be dispersed more evenly.
High knife tip speed	Knife tip speed of 8,705 fpm provides for a clean cut.
Cat. 4 driveline with over-running clutch	Upon disengaging the PTO, the over-running clutch allows the driveline to quit turning, while the clutch yoke, gearbox and rotor shaft slow down under their own inertia.
3 - "B" Section belts	"B" Section belts fit snug in the sheaves, and the multiple belts ensure positive transfer of power.
Baffles on the top inside of the deck	Keeps the cut material from clumping together, ensuring an even distribution of clippings.
Height adjusting roller	Rear height adjusting roller with greaseable bearings and tapered ends to prevent gouging during turns.
Standard scrapers on rear height adjusting roller	Keeps the roller clean for consistent cutting height.
Adjustable rear panel	Adjusts to allow strong discharge of material and aids in cleaning underside of deck.

Designs, specifications, features and information are subject to change without notice.