

## Features and Benefits

### Grooming Mowers, Rear Discharge

#### FDR3590 Model

Features	Benefits
<b>Cutting width</b>	90" Cutting width
<b>Gearbox HP rating</b>	25 - 60 HP
<b>Rear discharge</b>	The wide, even dispersal of grass leaves a fine thin layer directly behind the mower vs. a possible windrow to the side. Keeps grass from blowing in unwanted areas. Easier to mow around objects.
<b>Deflectors</b>	Built-in to throw material and debris down.
<b>Clevis type lower hitch points</b>	Allows for easy hook-up by being able to remove pins and back into clevises.
<b>Floating 3-point</b>	Top and bottom hitch points float up and down which allows the mower to float over uneven terrain.
<b>Frame-over-deck design</b>	Frames takes stress out of deck by supporting it.
<b>3/16" Deck thickness</b>	Heavy deck material to aid in overall strength and longevity. Reinforced spindle mounts.
<b>Lower hitch points adjust in and out</b>	Accommodates many tractor configurations by adjusting in and out.
<b>13" Semi solid tires with roller bearings</b>	13" Tires offer premium flotation. Roller bearings allow for a long life. Semi solid tires offer shock absorption.
<b>Heavy-duty Gauge wheel arms</b>	1/4" Gauge wheel arms increases strength.
<b>Non-aligned gauge wheels</b>	Rear wheels do not track behind the front wheels to reduce laying grass over.
<b>High blade tip speed</b>	18,500 fpm for cleaner cutting and better dispersion of clippings.
<b>Choice of Blades</b>	Low, medium or high lift blades are available to match the customer's desires and needs for his particular uses. Mulching blades also available.
<b>Fusion<sup>®</sup> edge on blades</b>	Stay sharper, longer
<b>Blade overlap</b>	Blade overlap of 2 1/4" assures no skipping in tight turns.
<b>Heavy-duty roller bearings &amp; 1 3/8" machined spindles</b>	Roller bearings for smooth running and quiet operation, 1 3/8" machined spindles for durability, balanced performance, and accuracy. Cast iron housings for added protection and durability.
<b>Top greasing spindles</b>	Assures top bearing gets greased. No shields to remove.
<b>Single C-section Kevlar belt</b>	Simple one belt design. Kevlar material adds additional strength.
<b>Spring loaded adjustable idler</b>	Allows for constant and proper pressure on the belt.
<b>Blade bar</b>	Bar gives additional support to blade.
<b>5 Year Limited Gear Box warranty</b>	Shows our confidence in the gearbox integrity. 5 year Parts & Labor with S/N 329841+.
<b>Driveline hanger</b>	For ease in hookup and storage of driveline. Keeps driveline off ground.
<b>Quick Hitch Compatible</b>	Compatible with Land Pride Quick Hitch (S/N 294658+) for easy attachment and removal and increased productivity.

*Designs, specifications, features and information are subject to change without notice.*