



FDR25 Series Rear Discharge Mowers

| Features | Benefits |
|--|---|
| 2 Cutting widths | 72" and 84" (1.83m and 2.13m) |
| Gearbox Horsepower Rating | 15 - 60 Horsepower (11.2kW - 44.7 kW) |
| Rear discharge | The wide, even dispersal of grass leaves a fine thin layer directly behind the mower, vs. a possible windrow to the side. Keeps grass from blowing in unwanted areas. Easier to mow around objects. |
| Deflectors | Built-in to throw material and debris down. |
| Clevis type lower hitch points | Allows for easy hook-up by being able to remove pins and back into clevises. |
| Floating 3-Point | Top and bottom hitch points float up and down which allows the mower to float over uneven terrain. |
| 5/16" (8mm) Rolled front on deck | 5/16" (8mm) roll formed front deck edging designed to take heavy abuse. |
| Frame-over-deck design | Frames takes stress out of deck by supporting it. |
| 3/16" (5mm) Deck thickness | Heavy deck material to aid in overall strength and longevity. Reinforced spindle mounts. |
| Lower hitch points adjust in and out | Accommodates many tractor configurations by adjusting in and out. |
| FDR2572 Only - Solid rubber tires with roller bearings | Solid rubber tires on the FDR2572 are sandwiched between the rim halves, bolted in, and can't go flat. Roller bearings allow for a long life. |
| FDR2584 Only - Semi solid tires with roller bearings | Semi solid tires on the FDR2584 offer premium flotation. Roller bearings allow for a long life. Semi solid tires offer shock absorption. |
| Heavy-duty Gauge wheel arms | 1/4" (6mm) Gauge wheel arms increase strength. |
| Non-aligned gauge wheels | Rear wheels don't track behind the front wheels to reduce laying grass over. |
| High blade tip speed | 72" (1.83m) = 18,130 fpm (92.1mps) For cleaner cutting and better dispersion of clippings. 84" (2.13m) = 17,210 fpm (87.4 mps) |
| Choices of blades | Low, medium, high-lift, or mulching blades are available to match customer needs and specific applications. |
| Blade overlap | Blade overlap of 1 1/4" (32mm) assures no skipping in tight turns. |
| 1 3/8" Machined blade spindle with ball bearings and cast iron housing. | Machined spindle for balanced performance and accuracy, ball bearings for smooth and quiet running, cast iron housing for added protection and durability. |
| Top greasing spindles | Assures top bearing gets grease. No shields to remove. |
| Single B-section Kevlar belt | Simple one belt design. Kevlar material adds additional strength. |
| Vacuum formed ABS belt guards | No scratching, no rattling. |
| Spring loaded adjustable idler | Allows for constant and proper tension on belt. Better than adjusting gearbox for belt tension. |
| Blade bar | Bar gives additional support to blade. (Not available on FDR2572) |
| Top Hitch | Top hitch has two hook-up points which allows greater lifting leverage for smaller tractors. |
| 5 Year Limited Gearbox warranty | Shows our confidence in the gearbox integrity. 5 year Parts & Labor with S/N 329841+. |
| Driveline hanger | For ease in hookup and storage of driveline. Keeps driveline off ground. |
| Quick Hitch Compatible | Compatible with Land Pride Quick Hitch for easy attachment and removal increases productivity. |