

## Rotary Tillers, Standard Tine Rotation

### RTA10 Series

Features	Benefits												
<b>American made</b>	Many tillers are imported. American made means better parts availability.												
<b>Tractor HP range</b>	17-25 HP												
<b>Gearbox Warranty</b>	5 Years on housing, gears, seals, and bearings. Shows our confidence in the product.												
<b>Working widths</b>	42", 50", 58" to meet a wide range of applications and needs.												
<b>6 1/2" Digging depth</b>	For deep soil penetration.												
<b>Plate steel upper hitch</b>	Plate steel is stronger than flat bar type hitch												
<b>Clevis hitch</b>	Provides additional strength and easy one person hook-up.												
<b>Hitch offset capability</b>	Offset by moving lower hitch points and gearbox mount to cover right tire track.												
<b>Offset Dimensions</b>	<table border="0"> <tr> <td><b>42" Width</b></td> <td>16" - 26" Std.</td> <td>13" - 29" Max. Right</td> <td>23" - 19" Max. Left</td> </tr> <tr> <td><b>50" Width</b></td> <td>25" - 25" Std.</td> <td>18" - 32" Max. Right</td> <td>32" - 18" Max. Left</td> </tr> <tr> <td><b>58" Width</b></td> <td>29" - 29" Std.</td> <td>22" - 36" Max. Right</td> <td>36" - 22" Max. Left</td> </tr> </table>	<b>42" Width</b>	16" - 26" Std.	13" - 29" Max. Right	23" - 19" Max. Left	<b>50" Width</b>	25" - 25" Std.	18" - 32" Max. Right	32" - 18" Max. Left	<b>58" Width</b>	29" - 29" Std.	22" - 36" Max. Right	36" - 22" Max. Left
<b>42" Width</b>	16" - 26" Std.	13" - 29" Max. Right	23" - 19" Max. Left										
<b>50" Width</b>	25" - 25" Std.	18" - 32" Max. Right	32" - 18" Max. Left										
<b>58" Width</b>	29" - 29" Std.	22" - 36" Max. Right	36" - 22" Max. Left										
<b>Fits Land Pride Quick-Hitch</b>	Allows for quick and easy one person hook-up. Does not offset with Quick-Hitch.												
<b>Adjustable Parking stand</b>	Easy hook-up and storage.												
<b>Adjustable Skid Shoes</b>	Control depth with seven adjustments.												
<b>Formed and reinforced rear deflector</b>	Keeps dirt in and leaves a level finish. Forming gives deflector additional strength. Adjustable deflector allows for various finish results.												
<b>4 'C' shaped tines per flange</b>	'C' Shaped tines require less HP to move through the ground.												
<b>Solid rotor shaft</b>	1 3/4" Solid steel rotor shaft for strength.												
<b>15" Rotor swing diameter</b>	For deep tilling and turning the soil over faster.												
<b>Double lip seal on rotor bearing</b>	Double lip seal helps keep the dirt out and the grease in.												
<b>Fully shielded shear pin or slip-clutch driveline</b>	Protects gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.												
<b>#80 Drive chain enclosed in oil bath</b>	Heavy drive chain stretches less, and oil bath keeps wear to a minimum.												
<b>Stamped chain cover</b>	Stamped forming gives the chain cover strength.												

*Designs, specifications, features and information are subject to change without notice.*

## Features and Benefits

### Rotary Tillers, Standard Tine Rotation

#### RTA15 Series

Features	Benefits																
American made	Many tillers are imported. American made means better parts availability.																
Tractor HP range	17 - 50 HP; Dependent upon width and Series of tiller.																
Gearbox warranty	5 Year on housing, gears, seals and bearings. Shows our confidence in the product.																
Working widths	50", 58", 66" & 74" to meet specific customer needs.																
6 1/2" Digging depth	For deep soil penetration.																
Plate steel upper hitch	Plate steel is stronger than flat bar type hitch.																
Clevis hitch	Provides additional strength and easy one person hook-up.																
Hitch sideshift capabilities	Sideshift tiller to cover right tire track. Gearbox slides with tiller.																
Sideshift dimensions	<table border="0"> <tr> <td>50" Width</td> <td>25" - 25" Std.</td> <td>12" - 38" Max. Right</td> <td>31" - 19" Max. Left</td> </tr> <tr> <td>58" Width</td> <td>29" - 29" Std.</td> <td>12" - 46" Max. Right</td> <td>35" - 23" Max. Left</td> </tr> <tr> <td>66" Width</td> <td>33" - 33" Std.</td> <td>12" - 54" Max. Right</td> <td>39" - 27" Max. Left</td> </tr> <tr> <td>74" Width</td> <td>37" - 37" Std.</td> <td>16" - 58" Max. Right</td> <td>43" - 31" Max. Left</td> </tr> </table>	50" Width	25" - 25" Std.	12" - 38" Max. Right	31" - 19" Max. Left	58" Width	29" - 29" Std.	12" - 46" Max. Right	35" - 23" Max. Left	66" Width	33" - 33" Std.	12" - 54" Max. Right	39" - 27" Max. Left	74" Width	37" - 37" Std.	16" - 58" Max. Right	43" - 31" Max. Left
50" Width	25" - 25" Std.	12" - 38" Max. Right	31" - 19" Max. Left														
58" Width	29" - 29" Std.	12" - 46" Max. Right	35" - 23" Max. Left														
66" Width	33" - 33" Std.	12" - 54" Max. Right	39" - 27" Max. Left														
74" Width	37" - 37" Std.	16" - 58" Max. Right	43" - 31" Max. Left														
Fits Land Pride Quick-Hitch	Allows for quick and easy one person hook-up. Does not offset to the left with Quick-Hitch.																
Adjustable Parking Stand	Allows for easy hook-up and storage.																
Adjustable Skid Shoes	Control depth with various settings.																
Formed and reinforced rear deflector	Forming gives deflector additional strength. Adjustable deflector allows for various finish results.																
4 'C' Shaped heat-treated tines per flange	'C' Shaped tines require less HP to move through the ground.																
RTA1550 & RTA1558 1 3/4" Solid steel rotor shaft	Solid steel shaft for strength.																
RTA1566 & RTA1574 2" Solid steel rotor shaft																	
15" Rotor swing diameter	For deep tilling and turning the soil over faster.																
Double lip seal on rotor bearing	Double lip seal helps keep the dirt out and the grease in.																
Cat. 3 heavy-duty fully shielded shear pin or slip-clutch driveline	Protects gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.																
#80 Drive chain enclosed in oil bath	Heavy drive chain stretches less, and oil bath keeps wear to a minimum.																
Stamped chain cover	Stamped forming gives the chain cover strength.																
Fully shielded shear pin or slip-clutch driveline	Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.																

*Designs, specifications, features and information are subject to change without notice.*