



**RTR1574 Series Rotary Tiller**

<b>Features</b>	<b>Benefits</b>
<b>American made</b>	Many tillers are imported. American made means better parts availability.
<b>Reverse tilling action</b>	Reverse action 'sucks' tiller into ground, does not walk on top of hard ground like forward rotation tillers can.
<b>Tractor Horsepower Range</b>	25 - 50 horsepower (18.6 - 37.3 kW); Dependent upon width and Series of tiller.
<b>Gearbox Warranty</b>	5 Years on housings, seals, bearings. Shows our confidence in the product.
<b>Working widths</b>	74" (1.88 m) To meet specific customers needs.
<b>6 1/2" (16.5 cm) Digging depth</b>	For deep soil penetration.
<b>Plate steel upper hitch</b>	Plate steel is stronger than flat bar type hitch.
<b>Clevis lower hitch</b>	Provides additional strength and easy one person hook-up.
<b>Hitch sideshift capabilities</b>	Sideshift tiller to cover right tire track. Gearbox slides with tiller.
<b>Sideshift dimensions 74" Width</b>	37" - 37" Std. (94 - 94 cm) 16" - 58" Max. Right (40.6 - 147.3 cm) 43" - 31" Max. Left (109 - 78.7 cm)
<b>Fits Land Pride Quick Hitch</b>	Allows for quick and easy one person hook-up. Does not offset to the left with Quick Hitch.
<b>Adjustable Parking stand</b>	Allows for easy hook-up and storage.
<b>Adjustable skid shoes</b>	Control depth with various settings.
<b>Formed and reinforced rear deflector</b>	Forming gives deflector additional strength. Adjustable deflector allows for various finish results.
<b>Front deflector</b>	Front deflector is flexible to take the beating from rocks or debris.
<b>4 'C' Shaped heat-treated tines per flange</b>	'C' Shaped tines require less horsepower to move through the ground.
<b>2" Solid steel rotor shaft</b>	Solid steel shaft for strength.
<b>15" (38 cm) Rotor swing diameter</b>	For deep tilling and turning the soil over faster.
<b>Double lip seal on rotor bearing</b>	Double lip seal helps keep the dirt out and the grease in.
<b>Cat. 3 heavy-duty fully shielded shear pin or slip-clutch driveline</b>	Protects gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.
<b>#80 Drive chain enclosed in oil bath</b>	Heavy drive chain stretches less, and oil bath keeps wear to a minimum.
<b>Stamped chain cover</b>	Stamped forming gives the chain cover strength.