

## Features and Benefits

### *Rotary Tillers, Reverse Tine Rotation*

#### RTR10 Series

Features		Benefits
<b>American made</b>		Many tillers are imported. American made means better parts availability.
<b>Gearbox Warranty</b>		5 Years on housing, seals, & bearings. shows our confidence in the product.
<b>Working widths</b>		42", 50", 58" to meet specific customer needs.
<b>Tractor HP range</b>		17-25 HP
<b>Reverse tilling action</b>		Reverse action 'sucks' tiller into ground, does not walk on top of hard ground like forward rotation tillers can.
<b>Front deflector</b>		Front deflector is flexible to take the beating from rocks or debris.
<b>Formed and reinforced rear deflector</b>		Keeps dirt in and leaves a level finish. Forming gives deflector additional strength. Adjustable deflector allows for various finish results.
<b>Adjustable skid shoes</b>		Control depth with seven adjustments.
<b>Solid rotor shaft</b>		1 3/4" Solid steel rotor shaft for strength.
<b>Double lip seal on rotor bearing</b>		Double lip seal helps keep the dirt out and the grease in.
<b>4 'C' shaped heat-treated tines per flange</b>		'C' Shaped tines require less HP to move through the ground.
<b>15" Rotor swing diameter</b>		For deep tilling and turning the soil over faster.
<b>6 1/2" Digging depth</b>		For deep soil penetration.
<b>Fully shielded shear pin or slip-clutch driveline</b>		Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.
<b>Stamped chain cover</b>		Stamped forming gives the chain cover strength.
<b>#80 Drive chain enclosed in oil bath</b>		Heavy drive chain stretches less, and oil bath keeps wear to a minimum.
<b>Adjustable parking stand</b>		Allows for easy hook-up and storage.
<b>Plate steel upper hitch</b>		Plate steel is stronger than flat bar type hitch.
<b>Clevis lower hitch</b>		Provides additional strength and easy one person hook-up.
<b>Adjustable lower hitch</b>		Offset unit to cover right tire track.
<b>Offset Dimensions</b>	<b>42" width</b>	16"-26" std. 13"-29" Maximum Right 23"-19" Maximum Left
	<b>50" width</b>	25"-25" std. 18"-32" Maximum Right 32"-18" Maximum Left
	<b>58" width</b>	29"-29" std. 22"-36" Maximum Right 36"-22" Maximum Left
<b>Fits Land Pride Quick-Hitch</b>		Allows for quick and easy one person hook-up. (Offset cannot be used with Quick-Hitch.)

*Designs, specifications, features and information are subject to change without notice.*

## Features and Benefits

### *Rotary Tillers, Reverse Tine Rotation*

#### RTR15 Series

Features		Benefits		
American made		Many tillers are imported. American made means better parts availability.		
Working widths		50", 58" To meet specific customers needs.		
Tractor HP Range		17 - 35 HP		
Gearbox Warranty		5 Years on housings, seals, bearings. Shows our confidence in the product.		
Reverse tilling action		Reverse action 'sucks' tiller into ground, does not walk on top of hard ground like forward rotation tillers can.		
Front deflector		Front deflector is flexible to take the beating from rocks or debris.		
Formed and reinforced rear deflector		Forming gives deflector additional strength. Adjustable deflector allows for various finish results.		
Adjustable skid shoes		Control depth with various settings.		
Solid rotor shaft		1 3/4" Solid steel shaft for strength.		
Double lip seal on rotor bearing		Double lip seal helps keep the dirt out and the grease in.		
4 'C' Shaped heat-treated tines per flange		'C' Shaped tines require less HP to move through the ground.		
15" Rotor swing diameter		For deep tilling and turning the soil over faster.		
6 1/2" Digging depth		For deep soil penetration.		
Cat. 3 Driveline		Cat. 3 Driveline with heavy-duty shear-bolt or slip-clutch		
Fully shielded shear pin or slip-clutch driveline		Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.		
Stamped chain cover		Stamped forming gives the chain cover strength.		
#80 Drive chain enclosed in oil bath		Heavy drive chain stretches less, and oil bath keeps wear to a minimum.		
Adjustable parking stand		Allows for easy hook-up and storage.		
Plate steel upper hitch		Plate steel is stronger than flat bar type hitch.		
Clevis lower hitch		Provides additional strength and easy one person hook-up.		
Hitch sideshift capabilities		Sideshift tiller to cover right tire track. Gearbox slides with tiller.		
Sideshift dimensions	50" width	25"-25" Std.	12"-38" Max. right	31"-19" Max. left
	58" width	29"-29" Std.	12"-46" Max. right	35"-23" Max. left
Fits Land Pride Quick-Hitch		Allows for quick & easy one person hook-up. Sideshift cannot be used with Quick-Hitch.		

*Designs, specifications, features and information are subject to change without notice.*