

Features and Benefits

Rotary Cutters, Single Deck

RCR25 Series

Features	Benefits
Surpassed rugged industry standards	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
Tractor HP range	3-point (2596 Model = 50 - 110 HP) & (2510 Model = 60 - 110 HP) Pull-type (2596 Model = 30 - 110 HP) & (2510 Model = 50 - 110 HP)
540 or 1000 RPM	Fits wider variety of tractors. (RCR2596 is 540 RPM only)
Gearbox HP rating	120 Horsepower on splitter gearbox and 60 HP on outboard gearboxes.
5 Year gearbox warranty	Shows our confidence in the gearbox integrity.
3 Gearboxes	Allows equal torque to be spread to left and right gearbox.
Splined rubber flex- couplers between the center and outboard gearboxes	Protects the driveline and gearboxes from hard objects in the blade path.
Constant Velocity U-Joint option on RCR2510 & RCRM2510 Pull-type	Reduces chatter and extends life of U-joint during turns.
Slip-clutch protection on main driveline	Slip-clutch is more convenient than shear-bolt, protects gearbox against sudden impact.
3-Point or Pull-type	Pull-type fits older tractors without a top link or smaller tractors without enough lift capacity. (RCR2596 3-point: Cat. 1 & 2) (RCR2510 & RCRM2510 3-point: Cat. 2 & 3)
High productive cutting width	RCR2596 cuts 8'-0" width. RCR2510 & RCRM2510 cuts 9'-10" width.
Fully welded 10 Gauge deck	Fully welded deck adds rigidity.
3/16" Sidewall thickness	Protects sidewalls from thrown objects.
Obstacle free underside	Underside of deck is free of reinforcement members which tend to allow material to lodge.
Round back design	Allows for cleaner and efficient discharge of material, helps eliminate damage to rear corners by not sticking out.
Dual leveling rods on Pull-type	Dual leveling rods eliminate deck twisting when going over uneven terrain.
Chain or rubber shield option	Reduces flying debris.
Full length skids with replaceable shoes	Adds reinforcement to side panels. Replaceable shoes allows for change before wearing through to weld-on piece.
Splined blade hub	Splined blade hub offers tight non-slipping attachment to output shaft.
3/16" Round stump jumper	Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft.
1" x 4" Blade bar	Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft.
1/2" x 4" Heat-treated blades	Heat-treated blades last longer than non-heat-treated blades.
1" Diameter cutting capacity	Aids in cutting small brush.
High Blade tip speed	RCR2596 (540 rpm) = 14,792 fpm RCR2510 (540 rpm) = 17,749 fpm RCRM2510 (1000 rpm) = 18,035 fpm Means Cleaner Cutting of material.
Laminated tires	Laminated tires can handle almost any condition.
Airplane tires (Pull-Type only)	Airplane tires offer smooth roadability.
Fits Land Pride Quick Hitch	Allows for quick and easy one person hook-up.

Designs, specifications, features and information are subject to change without notice.