

## Features and Benefits

### Rotary Cutters, Single Deck

#### RCR2660 and RCR2672 Models

Features	Benefits
<b>Surpassed rugged industry standards</b>	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
<b>5 Year gearbox warranty</b>	Shows Land Pride's confidence in gearbox integrity.
<b>110 HP gearbox</b>	A rugged heavy built gearbox capable of handling heavy cutting applications.
<b>Cat. 4 driveline with 4 plate slip-clutch</b>	Excellent gearbox protection with the slip-clutch slipping when encountering obstruction in the blade path. Standard slip-clutch offers convenience over shear-bolts.
<b>Cat. I or II 3-point hitch</b>	Allows use on a wider variety of tractors.
<b>Lower clevis type 3-point hitch</b>	Allows for ease of hook-up to tractor. Also adds additional strength allowing for an even pull from the tractor's lower arms, vs. pulling on a single pin design.
<b>Heavy 10 gauge deck construction</b>	Can withstand more abuse than lighter gauge decks.
<b>1/4" Side panels for overall reinforcement</b>	Also protects sides from debris being thrown against them from the blades.
<b>Fully welded deck</b>	Robotically welded. Adds additional strength and reduces rust.
<b>Extended front tapered deck</b>	Contains and discharges material better.
<b>Round back design</b>	Allows for more efficient handling and dispersing of material.
<b>9" Deck Height</b>	Allows cutter to handle heavy cutting conditions.
<b>2" to 12" Cutting height</b>	Provides for a wide range of cutting conditions.
<b>High cutting capacity</b>	Can cut brushy areas with saplings up to 3".
<b>Full length skids with replaceable shoes</b>	Full length skids protect side plate structure, replaceable shoes for convenience.
<b>1/2" x 4" Heat-treated free swinging blades</b>	Free swinging protects from obstructions. Heat-treated offers longer life.
<b>Splined blade bar</b>	Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft.
<b>3/16" Round stump jumper</b>	Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft.
<b>High blade tip speed</b>	60" = 12,384 fpm and 72" = 14,861 fpm
<b>3" Dia. cutting capacity</b>	Can aid in clearing brush.
<b>Rugged laminated tailwheel</b>	Can't go flat. Choice of single or dual combination.
<b>Chain or rubber shield option</b>	Located on front and rear. Reduces flying debris.

*Designs, specifications, features and information are subject to change without notice.*