

Features and Benefits

Rotary Cutters, Single Deck

RCR2660 and RCR2672 Models

Features	Benefits
Surpassed rugged industry standards	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
Tractor HP range	40 - 110 HP
5 Year gearbox warranty	Shows Land Pride's confidence in gearbox integrity.
Cat. 4 driveline with 4 plate slip-clutch	Excellent gearbox protection with the slip-clutch slipping when encountering obstruction in the blade path. Standard slip-clutch offers convenience over shear-bolts.
Cat. I or II 3-point hitch	Allows use on a wider variety of tractors.
Lower clevis type 3-point hitch	Allows for ease of hook-up to tractor. Also adds additional strength allowing for an even pull from the tractor's lower arms, vs. pulling on a single pin design.
Cutting widths	60" and 72"
Heavy 10 gauge deck construction	Can withstand more abuse than lighter gauge decks.
1/4" Side panels for overall reinforcement	Also protects sides from debris being thrown against them from the blades.
Fully welded deck	Robotically welded. Adds additional strength and reduces rust.
Extended front tapered deck	Contains and discharges material better.
Round back design	Allows for more efficient handling and dispersing of material.
9" Deck Height	Allows cutter to handle heavy cutting conditions.
2" to 12" Cutting height	Provides for a wide range of cutting conditions.
Full length skids with replaceable shoes	Full length skids protect side plate structure, replaceable shoes for convenience.
1/2" x 4" Heat-treated free swinging blades	Free swinging protects from obstructions. Heat-treated offers longer life.
Splined blade bar	Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft.
3/16" Round stump jumper	Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft.
High blade tip speed	60" = 12,384 fpm and 72" = 14,861 fpm
2 1/2" Dia. cutting capacity	Can aid in clearing brush.
Rugged laminated tailwheel	Can't go flat. Choice of single or dual combination.
Chain or rubber shield option	Located on front and rear. Reduces flying debris.

Designs, specifications, features and information are subject to change without notice.