

Rotary Cutters, Single Deck

RCR2684 Series

| Features | Benefits |
|--|---|
| Surpassed rugged industry standards | All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI. |
| Tractor HP Range | 60-110 HP. |
| 5 Year gearbox warranty | Shows Land Pride's confidence in gearbox integrity. |
| Cat. 4 driveline with 4 plate slip-clutch | Excellent gearbox protection with the slip-clutch slipping when encountering obstruction in the blade path. Standard slip-clutch offers convenience over shear-bolts. |
| Cat. II or III Three-point hitch | Allows use on a wider variety of tractors. |
| Available with single or dual tailwheels | Dual tailwheels offer greater stability in uneven terrain. |
| Cutting width | 84" |
| 1/4" Side panels for overall reinforcement | Also protects sides from debris being thrown against them from the blades. |
| Fully welded deck | Robotically welded. Adds additional strength and deck integrity. |
| Round back design | Allows for more efficient handling and dispersing of material. |
| Chain or rubber shield option | Located on front and rear. Reduces flying debris. |
| Full length skids with replaceable shoes | Full length skids protect side plate structure, replaceable shoes for convenience. |
| Splined blade bar | Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft. |
| 3/16" Oval stump jumper | Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft. |
| 1/2" x 4" Heat-treated free swinging blades | Free swinging protects from obstructions. Heat-treated offers longer life. |
| 2" Diameter cutting capacity | Can aid in clearing brush. |
| High blade tip speed | 14,369 fpm |
| Rugged laminated tailwheel | Can't go flat. |