

Features and Benefits

Rotary Cutters, Single Deck

RCR1884 Model

Features	Benefits
Surpassed rugged industry standards	All Land Pride Rotary Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
90 Hp gearbox	A rugged heavy built gearbox capable of handling heavy cutting applications.
5 Year gearbox warranty	Shows our confidence in the gearbox integrity.
Cat. 4 driveline with 2-plate slip-clutch	Slip-clutch driveline offers convenience for continual work.
Cat I or Cat II Hitch Quick Hitch Capability	Permits deck to follow the terrain for an even cut. Quick Hitch provides for fast hook-up.
Lower clevis type 3-point hitch	Allows for ease of hook-up to tractor. Also adds additional strength allowing for an even pull from the tractor's lower arms, vs. pulling on a single pin design.
84" Cutting width	Wide cutting width, Reduces cutting time in the field.
Heavy 10 gauge deck construction	Can withstand more abuse than lighter gauge decks.
Box tubing deck supports	Makes for a stronger rigid deck.
Fully welded deck	Adds additional strength.
Extended cutter front	For increased material flow and added protection.
Round back design	Helps discharge grass better than enclosed or partially enclosed cutter.
9 1/2" Deck Height	Allows cutter to handle heavy cutting conditions.
2" to 11" Cutting height	Provides for a wide range of cutting conditions.
1/4" x 2 1/2" Full length skid shoes	Provides sidewall reinforcement and full protection to bottom of sidewall.
1/2" x 4" Heat-treated free swinging blades	Free swinging protects from obstructions. Heat-treated offers longer life.
Splined blade bar hub	Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft.
10 Gauge stump jumper	Standard oval stump jumper slides over stumps, rocks and debris.
High blade tip speed	Ensures clean cut. (17,113 FPM)
2" Cutting capacity	Can aid in cleaning brush
Available with single or dual tailwheels	Dual tailwheels offer greater stability in uneven terrain.
15" Laminated tailwheel	Laminated material is long lasting in rough conditions.
Heavy-duty spindle on tailwheel	Tailwheels take a beating, 1 1/4" spindle gives the strength to protect tailwheel assembly.
Guarding	Protect against flying debris. Customer must choose to include chain or rubber on the front and rear. Rear Metal Band standard.

Designs, specifications, features and information are subject to change without notice.