

## Features and Benefits

### Primary Seeders

#### PS25 Series

Features	Benefits
<b>Cat. 2 3-Point Quick hitch adaptable</b>	Cat. 2 3-Point for larger tractors to handle the weight, or Pull-type for smaller tractors. Quick hitch allows for easy connecting and disconnecting.
<b>Machine weight</b>	2,940 lbs. (3-point)
<b>Front mounted wheels - Pull-type</b>	Front mounted wheels narrow the unit up for transport or going through gates.
<b>Side mounted wheels - Pull-type</b>	Side mounted wheels gives a smoother transport, and lowers the negative tongue weight.
<b>30 Bushel seed capacity</b>	30 Bushel is ideal for the sod farmer and grain growers.
<b>Seed level indicator</b>	Check seedbox level from the tractor seat.
<b>All welded weatherproof seedbox</b>	Keeps rain and rodents out, and gives rigidity to seedbox.
<b>Heavy-duty lock-up lid</b>	Lids are precision fit to keep seeds dry and rodents out and they won't buckle or slam shut in high winds.
<b>Lift hooks</b>	For easy loading on to trailers
<b>Transport locks - Pull-Type</b>	Keeps wheels in transport position if cylinders were to fail during transport.
<b>Vacuum sealed acremeter</b>	Vacuum sealed to keep dirt out. Acremeter to plan seed requirements.
<b>Fluted sprocket seed cups</b>	The right amount of seed is picked up by the fluted sprockets every time.
<b>Powder metal in the fluted sprocket</b>	Powder metal in the seed cup sprockets helps dissipate heat caused by the friction between the sprocket and housing.
<b>Adjustable seed opening</b>	Seed opening can be 'enlarged' by sliding a lever. Larger opening for fluffy seed allows for easier flow.
<b>Removable tongue on Pull-type</b>	Tongue is easy to remove. Convenient for storage or when loaded on a trailer.
<b>Cast iron packer wheels</b>	15 5/8" diameter front rings and 11 3/8" diameter rear rings are used to crush the clods and pack the seed in to promote seed to soil contact.
<b>Spring mounted rear packers</b>	Rear packer wheels are spring loaded for additional down pressure, and to stay in contact with the ground.
<b>#40 Roller chain</b>	All drives utilize #40 roller chain for smooth running.

*Designs, specifications, features and information are subject to change without notice.*