

Features and Benefits

Seeders, Primary Seeder

PSN2096 Model

Features	Benefits
Cat. 2 & 3, Cat. 2 Quick-Hitch adaptable	Cat. 2 & 3 offers a wide variety of tractors, Cat. 2 Quick-Hitch allows for easy connecting and disconnecting.
Seeding width	8'-6" Seeding width is just right for small acreage, roadside native grass work, and small turf farms.
Lift hooks	Lift hooks on each side of the seedbox to attach chain or strap to for easy loading and unloading.
Native Grass model	Native Grass model allows the user who works primarily with native grasses to use the main box for native grass seed.
Heavy-duty lids with stay open support	Lids are precision fit to keep seeds dry and rodents out and they won't buckle or slam shut in high winds.
Seed splash guard	Seedbox lid has a welded in guard to prevent seed from being spilled between lid and box.
Water tight Seedbox	All-welded seedbox construction prevents twisting from uneven ground, offers years of service. Keeps moisture out of the seedbox.
Large capacity native grass seedbox	1 Bushel per foot (8 1/2 bushel) capacity keeps filling to a minimum, Increases productivity.
Native grass seed cup	Large aluminum seed cup with aggressive picker wheel is used on Native Grass main box.
Native grass agitator	Native Grass main box uses an aggressive paddle style agitator to keep the fluffy native grass from bridging.
4-Speed transmission for Native Grass Seedbox	Easy and fast speed change, saves time from removing chains.
Seed rate adjustment lever for Standard Seeds Box and Small Seeds Box	Easy adjustment of seed rates. Lever positions are located on seed rate charts.
Seed rate decal	Positioned on lid of each box. Easy access to seed rate information.
High/Low seed settings	Easy adjustment on sprocket arrangement on seed cup drive. This allows for a very broad range of seed settings.
Ground driven metering	Front packer rollers are in constant contact with the ground to ensure consistent metering of seed. Seed metering stops automatically when front packer is raised off the ground.
Cast iron front packer rollers	12" diameter front rings and 9" diameter rear rings are used to crush the clods and pack the seed in to promote seed to soil contact.
Spring mounted rear packer rollers	Rear packer rollers are spring loaded for additional down pressure, and to stay in contact with the ground.
Adjustable track removers	Spring tine track removers effectively scratch out the tracks from the tractor tires.
#40 Roller chain	All drives utilize #40 roller chain for smooth running.

Optional Features (PSN2096 Primary Seeder)

Features	Benefits
Standard Seeds Box	A 0.6 bushel per foot standard seed box can be bolted to the front of the main box for seeding turf grass seeds. <ul style="list-style-type: none"> • Seed cups are powder metal flutes for accurate seed rates. • Seed agitator is paddle style to keep seeds from bridging.
Small Seeds Box	A bolt-on Small Seeds Box can be added to the rear of the main box to mix small seeds in with other types, allowing them to be seeded at rates that compliment each other.
Pull Type Hitch	Allows for easier hook-up to tractor, adaptable to smaller tractors.

Designs, specifications, features and information are subject to change without notice.