

Features and Benefits

All Flex Mowers

AFM4014 Model

Features	Benefits
Counter rotation on left hand deck	Spreads grass clippings more evenly.
Optional Slip clutch protection	Guards against premature gearbox failure. Protects mower deck spindles.
6" Deck overlap	Eliminates blade skips when turning. Tighter turns can be made.
Back wheels on side decks even with transportation tires	Allows the unit to be turned tighter without skips.
Rigid rear side deck tires	Holds hills and slopes better. Safer unit than the competition.
Removable transportation tire spindles	Allows a spindle to be replaced by simply removing two bolts.
High tip speed	Lifts the grass up for a better cut. Better discharge of material. Tip rates as high or higher than the competition.
Deflectors built into mower decks	Safety features meet ANSI standards. Many competitors use chains for protection. Once chains are removed the unit may not meet ANSI specifications.
Heavy center gearbox mounting plate	Handles start up torque.
Large flotation tires with sealant	18" Deck tires offer great flotation, less pounds per square inch.
Sleek frame design, including single beam hitch and compact deck overlap	Allows operator to make tighter runs without leaving windrows and skips. AFM virtually becomes a zero turn mower.
Gearbox warranty	S/N 368188- one year on all gearbox components. S/N 368188+ 5 years on gearbox housing, gears and shafts, 3 years on bearings and seals in gearbox.
Narrow transport width	6'-8" Transport width allows the unit to be transported with ease.
Low pivot points on deck	The lower the pivot points are to the ground, the more side to side swing, allowing for excellent flotation from each deck.
Gearbox HP Rating	40 - 70 HP
Automatic wing locks	When wings are raised in the full transport position, the wings lock in place, no need to get off the tractor to lock.
1/4" Gauge wheel arms	1/4" Sidewall thickness on gauge wheel arms means a great deal of 'hidden' strength.
Rear discharge	Even dispersal, discharged items are always aimed downward. No rear chains are needed, which tend to clump damp grass.
23" Transport tires with tapered bearings	23" Transport tires offer smooth roading. Tapered bearings offer longevity.
18,396 fpm Blade tip speed	High blade tip speed for clean cut and efficient discharge.
Cat. 4 CV main driveline	Constant velocity main driveline allows for tighter turns without harming U-joints in driveline.
Mulching blades	Mulching blades are available.
Cat. 2 slip-clutch wing drivelines	Reduces start-up torque that is put on the driveline, gearbox and gearbox support.
Easy belt tension release	Easily release belt tension for changing belt or for winter storage.
Easy to grease blade spindles	No guards to remove for routine greasing of blade spindles.

Designs, specifications, features and information are subject to change without notice.

Features and Benefits

All Flex Mowers

AFM4016 Model

Features	Benefits
Low pivot points on deck	The lower the pivot points are to the ground, the more side to side swing, allowing for excellent flotation from each deck.
Narrow 6'8" transport width	Not much wider than most tractors, making for safer transport. Meets most city/county codes for transport width.
Gearbox HP Rating	40 - 70 HP
8" Deck overlap	Eliminates skipping when going into a tight turn.
Automatic wing locks	When wings are raised in the full transport position, the wings lock in place, no need to get off the tractor to lock.
1/4" Gauge wheel arms	1/4" Sidewall thickness on gauge wheel arms means a great deal of 'hidden' strength.
Sleek frame design	Single beam hitch design allows for a zero turning radius.
Rear discharge	Even dispersal, discharged items are always aimed downward. No rear chains are needed, which tend to clump damp grass.
Blade rotation	Counter rotation; Wing decks throw grass away from the path of the rear deck. Rear deck doesn't get covered up nor does it get bogged down by cut grass.
18" Deck tires with sealant	18" Tires offer great flotation, less lbs. per square inch. Sealant minimizes flats.
23" Transport tires with tapered bearings	23" Transport tires offer smooth roading. Tapered bearings offer longevity.
18,340 fpm Blade tip speed	High blade tip speed for clean cut and efficient discharge.
Cat. 4 CV main driveline	Constant velocity main driveline allows for tighter turns without harming U-joints in driveline.
Mulching blades	Mulching blades are available.
Cat. 2 slip-clutch wing drivelines	Reduces start-up torque that is put on the driveline, gearbox and gearbox support.
Easy belt tension release	Easily release belt tension for changing belt or for winter storage.
Easy to grease blade spindles	No guards to remove for routine greasing of blade spindles.
Gearbox Warranty	S/N 368188- one year on all gearbox components. S/N 368188+ 5 years on gearbox housing, gears and shafts, 3 years on bearings and seals in gearbox.

Designs, specifications, features and information are subject to change without notice.