

Features and Benefits

Post Hole Diggers, Hydraulic

HD25 & HD35 Series (3-Point)

Features	Benefits
3-Point Cat. 1 or 2 Hitch	Fits a wider variety of tractors by fitting Cat. 1 & 2.
Bucket Mount Option	Easily bolt mounting plate to the side of the front loader bucket, and use the bucket to help push the auger into the ground
2 7/8" yoke tubing – schedule 40 pipe	3/16+ wall thickness for strength and durability.
3 1/2" Reinforced boom tubing	7/32" wall tubing for strength.
Auger flighting	Constant thickness on 1/4" flighting vs. tapered.
Replaceable hardened steel points on auger	Hardened points will last longer than non-hardened. Points can easily be replaced when worn or damaged. Cast steel auger fishtail tips.
25 Series	Use with tractor hydraulic systems that pump at 5 –12 GPM, at 1500 – 3000 PSI.
35 Series	Use with tractor hydraulic systems that pump at 10-25 GPM, at 1500 – 3000 PSI.
2" Output shaft	2" tackles the torque loads that can be transmitted from hard ground. Fairly standard size for the industry, fits many competitive augers.
5 Year gearbox warranty	Shows our confidence in the gearbox integrity.
Hydraulic hose	Standard on 3-point model, option on bucket mount due to distance varying on tractor models.
Auger Sizes	6", 9", 12", 15", 18" or 24"
Auger Length	48" standard size.

Designs, specifications, features and information are subject to change without notice.