

Features and Benefits

Rotary Cutters, Folding Deck

RCR3515 & RCRM3515 Models

Features	Benefits
Surpassed rugged industry standards	All Land Pride Rotary Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
Mostly factory assembled	Arrives for quick and easy set-up. Minimal time is wasted setting or prepping the unit.
5 Year gearbox warranty	Shows confidence in gearbox integrity.
Gearbox seal protection	Gearbox bottom seal protection for longer bearing life.
160 HP splitter gearbox	High gearbox rating for handling jobs suited for this Rotary Cutter.
110 HP center & wing gearboxes	High gearbox rating for 2" cutting capacity.
540 or 1000 RPM PTO speed	Fits wide variety of tractors in the 50 to 160 HP range.
4 Gearboxes vs. 3	Spreads overall weight out and evenly disburses horsepower to each spindle.
Low tongue weight	Ideal for smaller HP tractors by reducing the amount of weight on the drawbar.
Narrow tongue construction	Allows for a tighter turning radius.
Round back design	Allows for more efficient handling and dispersing of material.
Input Driveline: Cat. 5 CV	Driveline is matched just right for capacity of tractor. Constant velocity (CV) U-joint allows for 80 degree turns without doing damage to the driveline.
Wing driveline: Cat. 4 with slip-clutch	Driveline is sized right for the intended cutting capacity. Slip-clutch will slip under load instead of twisting the driveline. (Optional Cat. 5 driveline is available.)
Slip-clutch drivelines	Slip-clutches are designed to slip to minimize twist damage to the driveline profiles.
High Blade tip speed (See Specifications for actual FPM)	Allows clean cutting of material.
6" Blade overlap	Eliminates skipping during turns.
Left wing rotates clockwise	Better discharge of material. Picks up tractor tracks.
2" to 14" Cutting Height	Cover a wide range of cutting conditions.
3/16" Round stump jumper	Standard thick stump jumper material keeps damage to a minimum.
1/4" Sidewall thickness	Increased thickness reduces damage from objects being thrown into deck sidewalls.
Replaceable skid shoes	Skid shoes protect deck in uneven terrain. Can be easily replaced if damaged or worn out.
Self-leveling hitch	Reduces drawbar wear by keeping hitch level while going through ditches.
Hinged wing sections	Allows cutter to follow terrain. Ideal for rough ground where hillsides, ditches and hollows can cause uneven cutting.
1" Solid hinge rods	Larger diameter hinge rod gives greater strength to the cutter from front to rear, and in the hinge area itself.
Wing transport locks	Wing transport locks securely hold the wings in the folded position in case of hydraulic failure.
Enclosed front to rear dual leveling rods	Dual leveling rods enable the cutter to pull equally on the rear axle during travel over rough terrain.
5-Bolt hubs	5-Bolt hubs makes the wheel assembly more durable and longer lasting.
4 or 6 Wheels	Choice of laminated tires for eliminating flats, used aircraft tires for cushioning during field and road use or bare rims for supplying your own automotive tires.
Spring cushioned center-axle	Protects unit from bumps and ground shock.
Replaceable wheel spindles	Wheel spindles can be replaced when damaged without replacing the entire axle assembly.

Designs, specifications, features and information are subject to change without notice.

Features and Benefits

Rotary Cutters, Folding Deck

RCR3515 and RCRM3515 Models

Features and Benefits Of Optional Equipment	
4 or 6 Wheel option	Center deck wheels can be single (4-wheel option) or dual (6-wheel option). Dual wheels on the center deck provide better load distribution.
Wheel options	Laminated tires: Eliminates flats. Airplane tires without foam filling: Give better cushion while transporting. Airplane tires with foam filling: Give better cushion while transporting and can't go flat. 15" Wheel rims: Can mount your own tires.
Deck rings (optional)	3/8" x 3" full welded deck ring keeps blades from damaging the deck.
Front & rear shielding	Choice allows customer to fit his needs. Front Shielding: Rubber guard, single chain or double chain. Rear Shielding: Rubber guard, single chain or double chain.
Paint options	Choice of orange, red, green or tan to match popular tractor lines.

Designs, specifications, features and information are subject to change without notice.