

## Features and Benefits

### Rotary Cutters, Folding Deck

#### RC(M)5515 & RC(M)6515 Models

Features	Benefits
Surpassed rugged industry standards	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
Factory assembled	Saves customer set-up time and money.
5 Year gearbox warranty	Shows confidence in gearbox integrity.
Gearbox Seal Protection	Gearbox bottom seal protection for longer bearing life.
2 3/8" Output gearbox shaft	Large output shaft handles shock loads better.
250 HP Splitter gearbox	High gearbox rating for rough work and high horsepower tractors.
210 HP center & wing gearboxes 55 Series 65 Series	High gearbox rating for 3 1/2" cutting capacity and high horsepower tractors. Higher gearbox rating for 4" cutting capacity and high horsepower tractors.
540 or 1000 RPM PTO speed	Fits wide variety of tractors.
Input driveline: Cat. 5 CV	Holds up to shock loads and harsh mowing conditions.
Star profile drive shafts	Star profile spreads load out to many points on the shaft. More apt to resist bending and twisting under shock loads and harsh mowing conditions.
Easy Greasable drivelines	Drivelines have access holes for greasing the U-joints in the driveline and to grease the inner profiles.
4 Plate slip-clutch	Protects drivelines and gearboxes by slipping clutches rather than twisting the driveline when impacts are encountered.
High blade tip speed	Allows clean cutting of material.
6" Blade overlap	Eliminates skipping during turns.
High cutting capacity 55 Series 65 Series	Can cut brushy areas with saplings up to 3 1/2". Can cut brushy areas with saplings up to 4".
12" Deck height	Handles heavy cutting, which reduces balling-up of cut material under the deck.
Left wing rotates clockwise	Better discharge of material. Picks up tractor tracks.
2 to 14" Cutting height	Covers a wide range of cutting conditions.
3/16" Stump jumper backed with a 1" thick mounting bar	Heavy round stump jumper with bottom gearbox seal protector. Can hold up to tough conditions.
10 gauge smooth deck top	Reduces accumulation of debris and is easier and faster to clean.
7 Gauge smooth deck bottom	Heavy deck design holds up to harsh conditions. No bottom obstructions.
Deck rings (option)	Keeps blades from damaging the deck.
Replaceable 1/4" wing sidewall	Reduces debris piercing possibilities. Can be replaced if damaged.
Reversible / Replaceable skid shoes	Can be reversed for extended life and can be replaced when damaged or worn out.
Self-leveling hitch	Reduces drawbar wear by keeping hitch level while going through ditches.
Hinged wing sections	Allow you to shape the cutter to the job. Ideal for rough ground where hillsides, ditches and hollows can cause uneven cutting.
1" Solid hinge rods	Larger diameter hinge rod gives greater strength to the cutter from front to rear, and in the hinge area itself.
Wing transport locks	Holds transport wings in the folded-up position in case of hydraulic pressure loss.
Enclosed front to rear dual leveling rods	Dual leveling rods enable the cutter to pull equally on the rear axle during travel over rough terrain. Many competitors only use one leveling rod.
5-Bolt hubs	5-Bolt hubs makes the wheel assembly more durable and longer lasting.
Drain holes in wheel rims	Allows water to drain from wheels mounted on folded-up wings. Helps prevent paint deterioration and rusting to the wheel rims.
Spring-cushioned center-axle	Protects unit from bumps and ground shock.
Replaceable wheel spindles	Wheel spindles can be replaced when damaged without replacing the entire axle. Simply remove two bolts to replace damaged spindle.

*Designs, specifications, features and information are subject to change without notice.*

## Features and Benefits

### Rotary Cutters, Folding Deck

#### RC(M)5515 & RC(M)6515 Models

Features	Benefits
<b>Features and Benefits Of Optional Equipment</b>	
<b>Double swivel hitch</b>	Great for uneven terrain, reduces drawbar wear.
<b>Bar-tite hitch-</b>	Ideal hitch for extreme conditions. Clamps tight to the drawbar eliminating any drawbar wear.
<b>6 or 8 Wheel option</b>	Outer wing wheel can be single (6-wheel option) or dual (8-wheel option). Dual wheels on the outer wings are ideal when mowing in areas where the wings need to flex up hill. The outer wheels ride farther up the embankments and keeps the decks from gouging. Also, the extra wheels on the outer wing decks provide better load distribution.
<b>Wheel options</b>	<b>Laminated tires:</b> Eliminates flats. <b>Airplane tires without foam filling:</b> Give better cushion while transporting. <b>Airplane tires with foam filling:</b> Give better cushion while transporting and can't go flat. <b>15" Wheel rims:</b> Can mount your own tires.
<b>Walking Tandem</b>	Better flotation and smoother ride on rougher terrain.
<b>Deck rings (optional)</b>	1/2" x 3" full welded deck ring keeps blades from damaging the deck.
<b>Front &amp; rear shielding</b>	Choice allows customer to fit his needs. Front Shielding: Rubber guard, single chain or double chain. Rear Shielding: Rubber guard, single chain or double chain.
<b>Paint options</b>	Choice of orange, red, green or tan to match popular tractor lines.

*Designs, specifications, features and information are subject to change without notice.*