

Features and Benefits

Rotary Cutters, Folding Deck

RC(M)5515 & RC(M)6515 Models

| Features | Benefits |
|---|--|
| Surpassed rugged industry standards | All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI. |
| Factory assembled | Saves customer set-up time and money. |
| 5 Year gearbox warranty | Shows confidence in gearbox integrity. |
| Gearbox Seal Protection | Gearbox bottom seal protection for longer bearing life. |
| 250 HP Divider gearbox 210 HP center & wing gearboxes | A rugged heavy built gearboxes capable of handling heavy cutting applications. |
| 2 3/8" Output gearbox shaft | Large output shaft handles shock loads better. |
| Input driveline: Cat. 5 CV | Holds up to shock loads and harsh mowing conditions. |
| Star profile drive shafts | Star profile spreads load out to many points on the shaft. More apt to resist bending and twisting under shock loads and harsh mowing conditions. |
| Easy Greasable drivelines | Drivelines have access holes for greasing the U-joints and to grease the inner profiles. |
| 4 Plate slip-clutch | Protects drivelines and gearboxes by slipping clutches rather than twisting the driveline when impacts are encountered. |
| High blade tip speed (See Specifications for actual FPM) | Allows clean cutting of material. |
| 6" Blade overlap | Eliminates skipping during turns. |
| High cutting capacity 55 Series 65 Series | Can cut brushy areas with saplings up to 3 1/2". Can cut brushy areas with saplings up to 4". |
| Pre-cut chamber | Allows grass and vegetation to stand back up prior to cutting for a more complete cut. |
| 12" Deck height | Handles heavy cutting, which reduces balling-up of cut material under the deck. |
| Left wing rotates clockwise | Better discharge of material. Picks up tractor tracks. |
| 2" to 14" Cutting height | Covers a wide range of cutting conditions. |
| 3/16" Stump jumper backed with a 1" thick mounting bar | Heavy round stump jumper with bottom gearbox seal protector. Can hold up to tough conditions. |
| 10 gauge smooth deck top | Reduces accumulation of debris and is easier and faster to clean. |
| 7 Gauge smooth deck bottom | Heavy deck design holds up to harsh conditions. No bottom obstructions. |
| Deck rings (option) | Keeps blades from damaging the deck. |
| Replaceable 1/4" wing sidewall | Reduces debris piercing possibilities. Can be replaced if damaged. |
| Reversible/replaceable skid shoes | Can be reversed for extended life and replaced when damaged or worn out. |
| Self-leveling hitch | Reduces drawbar wear by keeping hitch level while going through ditches. |
| Hinged wing sections | Allow you to shape the cutter to the job. Ideal for rough ground where hillsides, ditches and hollows can cause uneven cutting. |
| 1" Solid hinge rods | Larger diameter hinge rod gives greater strength to the cutter from front to rear, and in the hinge area itself. |
| Wing transport locks | Holds transport wings in the folded-up position in case of hydraulic pressure loss. |
| Enclosed front to rear dual leveling rods | Dual leveling rods enable the cutter to pull equally on the rear axle during travel over rough terrain. Many competitors only use one leveling rod. |
| 5-Bolt hubs | 5-Bolt hubs makes the wheel assembly more durable and longer lasting. |
| Drain holes in wheel rims | Allows water to drain from wheels mounted on folded-up wings. Helps prevent paint deterioration and rusting to the wheel rims. |
| Spring-cushioned center-axle | Protects unit from bumps and ground shock. |
| Replaceable wheel spindles | Wheel spindles can be replaced when damaged without replacing the entire axle. Simply remove two bolts to replace damaged spindle. |
| Double swivel hitch option | Great for uneven terrain, reduces drawbar wear. |
| Bar-tite hitch option | Ideal for extreme conditions. Clamps tight to drawbar eliminating drawbar wear. |
| Wheel options | Laminated tires: Eliminates flats. Airplane tires without foam filling: Give better cushion while transporting. Airplane tires with foam filling: Give better cushion while transporting and can't go flat. |
| Walking Tandem option | Better flotation and smoother ride on rougher terrain. |
| Deck rings (optional) | 1/2" x 3" full welded deck ring keeps blades from damaging the deck. |

Designs, specifications, features and information are subject to change without notice.