

## Features and Benefits

### Straw Crimpers

#### CR25 Series

| Features                             | Benefits  |
|--------------------------------------|---|
| <b>Cat. 1 Hitch</b>                  | Fits Land Pride Quick Hitch, and stout enough to work with any Cat. 1 tractor.  |
| <b>72" width</b>                     | Mostly used in wide open spaces, 72" covers a nice width.   |
| <b>Plate steel 'A' frame</b>         | Plate steel offers greater strength from natural force applied downward from tractor top link.  |
| <b>Tubular Construction</b>          | 2 1/2" x 2 1/2" x 3/16" Tubing vs. angle iron offers greater strength as well as gives a better appearance.   |
| <b>Expanded metal in weight tray</b> | Adds safety over blade area, doesn't allow foreign weight object to fall into blade area.   |
| <b>Blades</b>                        | Blades are blunted just right to crimp the straw and not cut it, as well as disturbing the soil very little.  |
| <b>Blade attachment</b>              | Blades are independent of each other allowing for less side load torque on each blade during turns.   |
| <b>Blade hub greasing</b>            | Each blade hub has a grease zerk for smooth rotation.   |
| <b>Storage stands</b>                | Each corner has a storage stand to aid in off the ground storing, as well as aiding in hooking to the tractor.  |
| <b>Blade spacing</b>                 | Blades are spaced 6" apart to offer optimum crimping.   |
| <b>Optional Water Tanks</b>          | Easily add up to 600 lbs. to aid in compacted soil conditions. Can easily reduce weight by draining tank incrementally. Water tanks are safer due to precise fit and fastening vs. stacking inconsistent sized objects and difficulty in uniform fastening. |

*Designs, specifications, features and information are subject to change without notice.*