

## Features and Benefits

### *Aerators, Pasture*

#### AR2596 & AR2510 Models

Features	Benefits
<b>All Welded 4 x 4 Tubing Frame</b>	Makes for a very strong frame.
<b>4 x 4 x 5/16 Tongue With Clevis Hitch</b>	Built heavy duty to withstand side loads from the tines.
<b>Forged &amp; Heat Treated Through Steel Tines</b>	Forged and heat treated tines are very resistant to wear and breakage giving them a long life.
<b>Tines</b>	Tines are designed with a twist to lift while fracturing the soil sideways.
<b>Bolt-on Tines (2 Bolts Per Tine)</b>	Tines are easily replaceable with 2 bolts per tine.
<b>8" Maximum Tine Penetration</b>	Great penetration for aerating the soil. (Actual penetration depth is dependent on ground condition and added weight.)
<b>Heavy Duty Rotary Tine Hangers</b>	Designed to stand up to the rigors of hard rocky soil.
<b>Bearings Are Protected With 3/8" Skid Shoes on 3-Sides</b>	Protects bearings against hitting solid objects such as rocks and stumps. (Skid shoe protection is located on the front, bottom and back sides of bearings)
<b>Adjustable Rotors</b>	Rotors can be adjusted from 2 1/2, 5 and 7 1/2 degrees to meet customers needs. The greater the angle the harsher the shattering of soil.
<b>7 1/2" Tine Spacing (4/per Spool) AR2596 = 48 Tines Total AR2510 = 64 Tines Total</b>	Tines spaced 7 1/2" apart provides good coverage.
<b>Optional Weights Constructed of 740 lbs. Concrete Blocks With Lifting Lugs Built In</b>	AR2596 accepts up to 3 concrete blocks and AR2510 accepts up to 4 concrete blocks. Helps Aerator tines penetrate the ground.
<b>Optional Harrow Lift Package</b>	Lifts the Drag Harrow off the ground for transporting on roadways.
<b>Accessory Drag Harrow</b>	Provides a means to smooth out the ground behind the Aerator. Drag Harrow has three positions it can be used: Drag Mat, Light Penetration & Deep Penetration.
<b>Accessory Trailing Hitch</b>	Hitch is self leveling for pulling implements behind the Aerator.

*Designs, specifications, features and information are subject to change without notice.*