

Features and Benefits

Rotary Cutters, Single Deck

SC2660 & SC2672 Skid Steer Model

Features	Benefits
Surpassed Rugged Industry Standards	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
Low Volume Motor @ 11-16 gpm Medium Volume Motor @ 17-21 gpm High Volume Motor @ 22-27 gpm	Customer can chose one of three optional motors for his SC2660 cutter or one of two optional motors (medium and high volume) for his SC2672 cutter. This allows the cutter to fit a wide variety of Skid Steers. Also the deck can be upgraded to a different motor when owner upgrades his Skid Steer.
Two Year Gearbox & Motor Warranty	Shows Land Pride's confidence in the gearbox and motor.
Smooth Deck Top	No pockets to collect rain and dirt. Easy to clean.
1/4" Side Panels for Overall Reinforcement	Protects sides from debris being thrown against them from the blades.
Front and Rear Chain Shields	Single chain on the front and double chain on the rear. Reduces flying debris.
(Optional) Replaceable Skid Shoes	Protect side plate structure. Shoes are replaceable for convenience.
Splined Blade Bar	Allows for tight positive fit of stump jumper and blade bar to motor output shaft.
3/16" Round Stump Jumper	Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft.
1/2" x 4" Heat-treated Free Swinging Blades	Heat-treated blades offer longer life. Free swinging blades protect from obstructions.
2" Diameter Cutting Capacity	Can aid in clearing brush.
SC2660 High Blade Tip Speed	Low volume motor = 18,540 fpm at 16 gpm. Medium volume motor = 18,850 fpm at 21 gpm. High volume motor = 19,000 fpm at 27 gpm.
SC2672 High Blade Tip Speed	Medium volume motor = 17,200 fpm at 21 gpm. High volume motor = 18,550 fpm at 27 gpm.
Offset Hitch (8 1/2" to the right)	Allows the operator to cut close to obstacles on the right side.
Optional Front Gauge Wheel	Provides easy operation and handling over uneven terrain, laminated tire can't go flat.
Floating Hitch Mounting Plate	Allows smoother travel over rough terrain with the optional gauge wheel easing the fatigue put on the operator.
Optional Operator Protection Door	Provides additional operator protection from flying objects.
Lift Limit Safety Chain	Provides additional operator protection from flying objects by allowing the Rotary Cutter to only be lifted up to 18".

Designs, specifications, features and information are subject to change without notice.