

**SC26 Series (Skid Steer)**

Features	Benefits
<b>Surpassed rugged industry standards</b>	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
<b>Low volume motor @ 11-16 gpm Medium volume motor @ 17-21 gpm High volume motor @ 22-27 gpm</b>	Customer can chose one of three optional motors for his SC2660 cutter or one of two optional motors (medium and high volume) for his SC2672 cutter. This allows the cutter to fit a wide variety of Skid Steers. Also the deck can be upgraded to a different motor when owner upgrades his Skid Steer.
<b>Two year gearbox &amp; motor warranty</b>	Shows Land Pride's confidence in the gearbox and motor.
<b>Case drain</b>	Protects gearbox.
<b>Smooth top 14 ga deck with 10 ga. bottom deck</b>	No pockets to collect rain and dirt. Easy to clean. Superior double deck construction.
<b>1/4" Side panels for overall reinforcement</b>	Protects sides from debris being thrown against them from the blades.
<b>Side discharge</b>	Allows material to be discharged away from operator.
<b>Front and rear chain shields</b>	Single chain on the front and double chain on the rear. Reduces flying debris.
<b>Replaceable skid shoes (optional)</b>	Protect side plate structure. Shoes are replaceable for convenience.
<b>Splined blade bar</b>	Allows for tight positive fit of stump jumper and blade bar to motor output shaft.
<b>3/16" Round stump jumper</b>	Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft.
<b>1/2" x 4" Heat-treated free swinging blades</b>	Heat-treated blades offer longer life. Free swinging blades protect from obstructions.
<b>2" Diameter cutting capacity</b>	Can aid in clearing brush.
<b>SC2660 High blade tip speed</b>	Low volume motor = 18,540 fpm at 16 gpm. Medium volume motor = 18,850 fpm at 21 gpm. High volume motor = 19,000 fpm at 27 gpm.
<b>SC2672 High blade tip speed</b>	Medium volume motor = 17,200 fpm at 21 gpm. High volume motor = 18,550 fpm at 27 gpm.
<b>Offset hitch (8 1/2" to the right)</b>	Allows the operator to cut close to obstacles on the right side.
<b>Optional front gauge wheel</b>	Provides easy operation and handling over uneven terrain, laminated tire can't go flat.
<b>Floating hitch mounting plate</b>	Allows smoother travel over rough terrain with the optional gauge wheel easing the fatigue put on the operator.
<b>Operator protection door (optional)</b>	Provides additional operator protection from flying objects.
<b>Lift limit safety chain</b>	Provides additional operator protection from flying objects by allowing the Rotary Cutter to only be lifted up to 18".