

### RCF2060 & RCF2072 Models

<b>Features</b>	<b>Benefits</b>
<b>Surpassed rugged industry standards</b>	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
<b>5 Year gearbox warranty</b>	Shows our confidence in the gearbox integrity.
<b>Gearbox Seal Protection</b>	Gearbox bottom seal protection for longer bearing life.
<b>Cat. 3 driveline with shear-bolt Option</b>	Shear-bolt offers maximum driveline protection.
<b>Cat. 3 driveline with 2-plate slip-clutch Option</b>	Slip-clutch driveline offers convenience for continual work.
<b>Dual position clevis type 3-point floating top link</b>	Permits deck to follow the terrain for an even cut.
<b>Lower clevis type 3-point hitch</b>	Allows for ease of hook-up to tractor. Also adds additional strength allowing for an even pull from the tractor's lower arms, vs. pulling on a single pin design.
<b>Heavy 10 gauge deck &amp; side skirt construction</b>	Can withstand more abuse than lighter gauge decks.
<b>Box tubing deck supports</b>	Makes for a stronger rigid deck.
<b>Fully welded deck</b>	Adds additional strength.
<b>Extended cutter front</b>	For increased material flow and added protection.
<b>Round back design</b>	Helps discharge grass better than enclosed or partially enclosed cutters.
<b>Deck Height</b>	9 11/16" Deck height on 60" and 11" deck height on 72" model Allows cutter to handle heavy cutting conditions.
<b>1 1/2" to 12" Cutting height</b>	Provides for a wide range of cutting conditions.
<b>Full length skid shoes</b>	Provides sidewall reinforcement and full protection to bottom of sidewall.
<b>1/2" x 3" Heat-treated free swinging blades</b>	Free swinging protects from obstructions. Heat-treated offers longer life.
<b>Splined blade bar hub</b>	Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft.
<b>10 Gauge stump jumper</b>	Standard round stump jumper slides over stumps, rocks, and debris.
<b>High blade tip speed</b>	Ensures clean cut.
<b>15" Laminated tailwheel</b>	Laminated material is long lasting in rough conditions. Can't go flat.
<b>4" x 16" Solid rubber tailwheel</b>	Can't go flat.
<b>1 1/4" Heavy-duty spindle on tailwheel</b>	Tailwheels take a beating, spindle gives the strength to protect tailwheel assembly.
<b>Optional Guarding</b>	Protect against flying debris. Customer can choose to include single chain or rubber guarding on the front and back. Rear Metal Band standard on the back.
<b>Driveline Holder</b>	Keeps driveline up out of dirt. Easier hook up of driveline.