

## Features and Benefits

### Rotary Cutters, Folding Deck

#### RCC5615 & RCCM5615 Models

Features	Benefits
Surpassed rugged industry standards	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures.
Factory assembled	Saves customer set-up time and money.
5 Year gearbox warranty	Shows confidence in gearbox integrity.
250 HP Divider gearbox 210 HP center & wing gearboxes	A rugged heavy built gearboxes capable of handling heavy cutting applications.
Gearbox Seal Protection	Gearbox bottom seal protection for longer bearing life.
2 3/8" Output gearbox shaft	Large output shaft handles shock loads better.
Input driveline: Cat. 5 CV	Holds up to shock loads and harsh mowing conditions.
Easy Greasable drivelines	Drivelines have access holes for greasing the U-joints and to grease the inner profiles.
2 or 4 Plate slip-clutch	Protects drivelines and gearboxes by slipping clutches rather than twisting the driveline when impacts are encountered.
High blade tip speed (See Specifications for actual FPM)	Allows clean cutting of material and even distribution.
6" Blade overlap	Eliminates skipping during turns.
High cutting capacity	Can cut brushy areas with saplings up to 3 1/2".
High cutting capacity	Can cut brushy areas with saplings up to 3 1/2".
12" Deck height	Handles heavy cutting, which reduces balling-up of cut material under the deck.
Left wing rotates clockwise	Better discharge of material. Picks up tractor tracks.
3/16" Stump jumper backed with a 1" thick mounting bar	Heavy round stump jumper with bottom gearbox seal protector. Can hold up to tough conditions.
10 gauge smooth deck top	Reduces accumulation of debris and is easier and faster to clean.
7 Gauge smooth deck bottom	Heavy deck design holds up to harsh conditions. No bottom obstructions.
Replaceable 1/4" side skirt	Reduces debris piercing possibilities. Can be replaced if damaged.
Self-leveling hitch	Reduces drawbar wear by keeping hitch level while going through ditches.
Hinged wing sections	Allows cutter to follow terrain. Ideal for rough ground where hillsides, ditches and hollows can cause uneven cutting.
1" Solid hinge rods	Larger diameter hinge rod gives greater strength to the cutter from front to rear, and in the hinge area itself.
Wing transport lock pins	Holds transport wings in the folded-up position in case of hydraulic pressure loss.
Enclosed front to rear dual leveling rods	Dual leveling rods enable the cutter to pull equally on the rear axle during travel over rough terrain. Many competitors only use one leveling rod.
Adjustable Wheel Spacing	Wheel spacing can be adjusted to fit most standard row crop spacings.
5-Bolt hubs	5-Bolt hubs makes the wheel assembly more durable and longer lasting.
Drain holes in wheel rims	Allows water to drain from wheels mounted on folded-up wings. Helps prevent paint deterioration and rusting to the wheel rims.
Spring-cushioned trailing arms	Provides independent suspension, cushions loads on drawbar.
Replaceable wheel spindles	Wheel spindles can be replaced when damaged without replacing the entire axle. Simply remove one bolt to replace damaged spindle.
Pre-cut chamber	Allows grass and vegetation to stand back up prior to cutting for a more complete cut.
Reinforced leading edge	Front of deck can withstand heavy brush and saplings.
Collapsible leveling rods	Prevents damage and failure to leveling rods.
1" Leveling rods	Large diameter leveling rods provide superior supporting strength over rough terrain.
Double swivel hitch option	Great for uneven terrain, reduces drawbar wear. Must use spacer washers on drawbar.
Bar-tite hitch option	Ideal for extreme conditions. Clamps tight to drawbar eliminating drawbar wear.
Wheel options	<b>Laminated tires:</b> Eliminates flats. <b>Airplane tires without foam filling:</b> Give better cushion while transporting. <b>Airplane tires with foam filling:</b> Give better cushion while transporting and can't go flat.

*Designs, specifications, features and information are subject to change without notice.*