

RC4615 and RCM4615 Models

Features	Benefits
Surpassed rugged industry standards	All Land Pride Rotary Cutters have been designed and tested and meet rigorous voluntary testing procedures according to ISO 4254-13.
Factory assembled	Arrives for quick and easy set-up. Minimal time is wasted setting or prepping the unit.
7 Year gearbox warranty	Shows confidence in gearbox integrity. (Years 6 & 7, parts only.)
Rugged heavy built gearboxes	Capable of handling heavy cutting applications.
Gearbox seal protection	Gearbox bottom seal protection for longer bearing life.
2 Piece shield on wing gearboxes	Driveline grease zerks are easier to access.
LP Performance self-leveling hitch	Reduces drawbar wear by keeping hitch level while going through ditches.
Low hitch weight on tractor tongue	Ideal for smaller hp tractors by reducing the amount of weight on the drawbar.
Narrow A-frame hitch	Allows for a tighter turning radius.
Adjustable park jack angle	Park jack can be adjusted to be perpendicular to the ground.
Adjustable driveline hanger	Serves as a support rest for the driveline when the cutter is unhooked from the tractor. Assist operator when attaching driveline to power take-off shaft.
Input driveline: Cat. 6 CV	Driveline is matched just right for capacity of tractor. Constant velocity (CV) U-joint allows for 80 degree turns without doing damage to the driveline.
Drivelines with slip-clutches: Cat. 5 intermediate Cat. 4 Wings	Driveline is sized right for the intended cutting capacity. Slip-clutches will slip under load to minimize twist damage to driveline profiles.
Grease zerks on end caps of driveline cross journals	Intermediate and wing driveline cross journals are easier to grease.
High Blade tip speed	Allows clean cutting of material.
6" Blade overlap	Eliminates skipping during turns.
Left wing rotates clockwise	Better discharge of material. Picks up tractor tracks.
3/16" Round stump jumper	Standard thick stump jumper material keeps damage to a minimum.
Smooth Top Design	Allows for easy cleaning of deck.
Deck sheet tops are 100% welded	Makes center decks and wing decks stronger.
1/4" Sidewall thickness	Increased thickness reduces damage from objects being thrown into deck sidewalls.
Beveled skid shoes on wings	Reduces gouging the ground when turning.
Hinged wing sections	Allows cutter to follow terrain. Ideal for rough ground where hillsides, ditches, and hollows can cause uneven cutting.
1" Solid hinge rods	Larger diameter hinge rod gives greater strength to the cutter from front to rear, and in the hinge area itself.
Wing transport locks	Wing transport locks will hold wings in the folded position in the event of hydraulic loss.
Enclosed dual leveling rods	Cutter pulls equally on the rear axle while traveling over rough terrain.
5-Bolt hubs on trailing arms	5-Bolt hubs makes the wheel assembly more durable and longer lasting.
Drain holes in wheel rims	Allows water to drain from wheels mounted on folded-up wing. Helps prevent paint deterioration and rusting to the wheel rims.
Spring-cushioned trailing arms	Provides independent suspension, cushions loads on cutter and tractor drawbar.
Replaceable wheel spindles	Wheel spindles can be replaced when damaged without replacing entire axle assembly.
Wheel options	Laminated tires: Eliminates flats. Air filled tires: Give better cushion while transporting. Foam-filled tires: Give better cushion while transporting and can't go flat.
LP performance hitch option	Great for uneven terrain, reduces drawbar wear. Hitch pivots freely up and down and pivots about the tractor drawbar.
Bar-tite hitch option	Ideal for extreme conditions. Clamps tight to drawbar eliminating drawbar wear.
Roadway light kit option	Allows operator to transport on public roads safer.
Deck ring option	Keeps blades from damaging the deck.