

Features and Benefits

Zero Turn Mowers

ZXT54 & ZXT60 Series

Features	Benefits
54 or 60" Cutting width	Sized right and priced right for high-end residential and cost conscious ranchers, farmers, estate owners, and commercial operators.
1" to 5" Cutting height	Cutting height in 1/4" increments for good cutting height range control.
49" Outside drive tire stance	Provides excellent stability over uneven and hilly ground along with good maneuverability.
High Ground speed	Forward 11 mph and reverse 5.5 mph for high productivity.
Adjustable steering levers with comfort grip handles	Wide range of adjustments to accommodate almost any size of operator. Grips are designed for operator comfort and sustained productivity.
Stronger clean frame design	Integral frame and hydraulic reservoir construction reduces component clutter under the seat for easy cleanout and service access.
Single welded 10 gauge deck frame with reinforced edges	Makes a stronger deck and reduces unwanted flex.
Rapid deck height adjustment	The foot operated with spring assist deck lift and deck stop locator makes for a quick and easy precise cutting height adjustments.
Easy clean-out deck top	Deck allows air and debris move across the top for improved belt cooling and easy clean out.
Excellent trim capability	49" wheel stance provides for good trim capability especially when equipped with a 60" deck.
Mid-mount deck design	Puts deck closer to operator's line of sight for more efficient and precise operation.
Floating deck design	Chain suspension design provides excellent flotation over uneven terrain.
Four anti-scalp rollers	Two located on deck ends and two located toward mid-decks keeps scalping to a minimum.
Completely independent twin hydrostatic drives	Outboard heavy-wall tubular frame members also serve as independent left and right side hydraulic reservoirs for hydrostatic drive motors and fan cooled hydrostatic pumps located on each side of the machine eliminating the possibility of cross-contamination.
Premium wide stance drive tires	Provide excellent traction, outstanding side-hill stability and a smooth ride. (23x10.5-12)
Front ribbed tires mounted in heavy duty pivoting caster forks	Provide for a quick and durable turning response. (13 x 5-6 ribbed tires).
Lockable floating front axle.	Floating front axle provides for smoother ride, more uniform cut, and optimal traction capability by keeping all tires equally in contact with the ground over uneven terrain. Axle lock provides for temporary curb or edge cutting without grounding or hanging up the deck.
Electric clutch control	Provides an easy smooth engagement of the mower blade drive system.
Kevlar drive belts	Drive belts made with Kevlar™ fiber provide long belt life. One hydrostatic pump drive belt and one deck drive belt is easier to maintain and not as expensive as multiple belt designs.
1 3/8" blade spindles mounted in ductile iron housings	Blade spindles and spindle housings are designed to handle heavy shock loads.
Accessible blade spindle zerks	Makes greasing the blade spindles easy.
Heavy duty heat treated Fusion® high lift blades	Made from highest quality .25" thick fusion treated steel for high wear and increase blade life. High lift design stands grass up before cutting.
High blade tip speed	18,515 fpm on the 54" deck and 18,700 fpm on the 60" deck for clean quality of cut.
Choice of engines	Proven 26 hp Briggs and Stratton ELS, or 27 hp Kawasaki engines to meet customer preferences with power and performance to spare.
Electric start with choke control	Keyed ignition and manual choke control are placed for one-handed starting convenience.
Engine oriented for easy access	Easy access to oil dipstick, spark plugs, oil drain ports, air filters and oil filters for convenient serviceability.
Center mounted rear engine placement	Provides maximum mower stability, easy service access, increased leg room, and increased air flow around engine fins to extend engine life.

Designs, specifications, features and information are subject to change without notice.

Features and Benefits

Zero Turn Mowers

ZXT54 & ZXT60 Series

Engine air filtration	Premium Honda and Kawasaki engines come standard with a remote air intake which filters out 95 percent of airborne particles. The Briggs ELS comes standard with a proven 2-stage quick access filter cartridge.
Isolated exhaust muffler	Muffler is hidden and tucked down under to reduce noise and provide protection against burns
Ergonomically designed control console	Instrumentation and console controls are positioned for easy visual or fingertip access.
Hour meter	Measure actual engine run time to monitor service intervals.
Sleek styling twin six gallon fuel tanks with extra large fuel caps	12 Gallon fuel capacity for plenty of operating range and decreased down time. Extra large fuel openings for easy fueling. Fuel caps are placed inboard and center mounted to protect caps from damage and prevent overflow spills on inclines.
Fuel selector/shutoff valve	Provides on the go switching from one tank to another giving the operator time to finish the mowing job and to return to the refueling source before the mower stops running. Both tanks can be shutoff with this valve for servicing and storage.
Molded-in dual cup holders and storage compartments	Tanks are molded with cup holders that fit a wide variety of cups and are in easy access to the driver. A storage compartment molded next to the cups offer additional operator convenience.
Lever activated park brake	A manually activated over-center lever next to the operator's seat easily and conveniently activates or releases a highly durable and reliable enclosed wet disc brake. Mower will not move until brake is released.
Hinged seat platform	Provides easy service access without tools.
Comfortable adjustable seat	Deluxe Cushion with/without spring suspension or Molded Vinyl with suspension and adjustable positioning for operator comfort and sustained productivity.
Seat safety interlocks	Rising off of the seat with blades engaged will cut engine power and stop blade rotation. Engine cannot be started with blade engagement switch in "on" position.
Hinged floor platform	Provides quick and convenient service access to topside deck components without tools.
Certified ROPS	Certified folding ROPS for added operator protection.
Sun Canopy	An optional folding soft sun canopy is available to fit fixed or folding ROPS.
Snow Plow	An optional 60" or 72" motion activated snow plow is available for snow removal and year round usage. Mower deck does not need to be removed to attach the snow plow.
EPA Compliant Mowers	
EPA approved six gallon fuel tanks with sight gauge, extra large tethered fuel caps and vent valve	12 Gallon fuel capacity for plenty of operating range and decreased down time. Extra large fuel openings for easy fueling. Fuel caps are EPA approved, non vented, placed inboard and center mounted to protect caps from damage and prevent overflow spills on inclines. EPA vent valve help stops fuel leaks in rollover accidents and sight gauge makes it easy to see low fuel level in tanks.
Fuel tanks are vented to the engine carburetor	Engine burns fuel vapors instead of vapors leaking into the atmosphere.

Designs, specifications, features and information are subject to change without notice.