

Features and Benefits

Zero Turn Mowers

ZT60i & ZT72i Accu-Z®

| Features | Benefits |
|--|--|
| 60" or 72" cutting width | Sized right and priced right for ranch, estate owners, and commercial operators. |
| 1" to 5" Cutting height | Provides a good range of cutting heights in 1/4' increments for any type of turf grass. |
| 57 3/4" Outside drive tire stance | Provides excellent stability over uneven and hilly ground along with good maneuverability. |
| High ground speed | Forward 13 mph and reverse 6 mph for high productivity. |
| Adjustable steering levers with comfort grip handles | Wide range of adjustments to accommodate almost any size of operator. Grips are designed for operator comfort and sustained productivity. |
| Stronger clean frame design | Integral frame and hydraulic reservoir construction eliminates the need for cooling fans providing for cleaner and uncluttered component design. |
| Strong deck design | New manufactured deck design has a great appearance on the outside, but tough parts on the inside. 10 Gauge deck with 11 gauge doubler plate, and a reinforced front edge. |
| Rapid deck height adjustment | The foot operated with spring assist deck lift and deck stop locator makes for a quick and easy precise cutting height adjustments. |
| Easy clean-out deck top | Deck allows air and debris move across the top for improved belt cooling and easy clean out. |
| Excellent trim capability | Provides for good trim capability. |
| Mid-mount deck design | Puts deck closer to the operator's line of sight for more efficient and precise operation. |
| Floating deck design | Chain suspension design provides excellent flotation over uneven terrain. |
| Four anti-scalp rollers | Two located on deck ends and two located toward mid-decks keeps scalping to a minimum. |
| Completely independent twin hydrostatic drives | Outboard heavy-wall tubular frame members also serve as left and right side independent hydraulic oil reservoirs for the hydrostatic drive motors and pumps on each side of the machine eliminating the possibility of cross-contamination. |
| Premium wide stance drive tires | Provide excellent traction, outstanding side-hill stability and a smooth ride. (24x12.00-12 4ply) |
| Front ribbed tires mounted in heavy duty pivoting caster forks | Provide for a quick and durable turning response. (13x6.5-6 ribbed tires) |
| Tele-Caster® wheel spindles | Spring loaded caster wheel spindles for superior shock absorption over rough terrain. |
| Lockable floating front axle | Floating front axle provides for smoother ride, more uniform cut, and optimal traction capability by keeping all tires equally in contact with the ground over uneven terrain. Axle lock provides for temporary curb or edge cutting without grounding or hanging up the deck. |
| Electric clutch control | Provides an easy smooth engagement of the mower blade drive system. |
| Kevlar drive belts | Drive belts made with Kevlar™ fiber provide long belt life. One hydrostatic pump drive belt and one deck drive belt is easier to maintain and not as expensive as multiple belt designs. |
| 1" blade spindles mounted in ductile iron housings | Additional 3/16" plate steel is added to the deck connecting the blade spindle housing mounts. Blade spindles, spindle housings and mounts are designed to handle heavy shock loads. |
| Accessible blade spindle zerks | Makes greasing the blade spindles easy. |
| Heavy duty heat treated Fusion® high lift blades | Made from highest quality .25" thick fusion treated steel for high wear and increase blade life. High lift design stands grass up before cutting. |
| High blade tip speed | Provides a clean quality cut. (60" deck = 18,350 fpm & 72" deck = 18,800 fpm) |
| Choice of engines | Proven Kawasaki engines meets customer preferences with power and performance to spare. (60" Deck: = 23.5 hp or 27 hp Kawasaki and 72" Deck: = 27 hp Kawasaki) |
| Electric start with choke control | Keyed ignition and manual choke control are placed for one-handed starting convenience. |
| Engine oriented for easy access | Spark plugs, air filter, oil filter, & oil drain are placed easily within reach. |
| Center Mounted Rear Engine | Provides maximum mower stability, easy service access, increased leg room, and increased air flow around engine fins to extend engine life. |
| Remote Air Intake | All engines come standard with cyclonic type remote air intake to keep engines running clean and running longer. |
| Engine oil cooler | Keeps engine running at peak performance in warm weather conditions. |

Designs, specifications, features and information are subject to change without notice.

Features and Benefits

Zero Turn Mowers

ZT60i & ZT72i Accu-Z[®]

| | |
|---|--|
| Isolated exhaust muffler | Muffler is hidden and tucked down under to reduce noise and provide protection against burns. |
| Ergonomically designed control console | Instrumentation and console controls are positioned for easy visual or fingertip access. |
| Hour meter | Measure actual engine run time to monitor service intervals. |
| Sleek styling twin six gallon fuel tanks with extra large fuel caps | 12 Gallon fuel capacity for plenty of operating range and decreased down time. Extra large fuel openings for easy fueling. Fuel caps are placed inboard and center mounted to protect caps from damage and prevent overflow spills on inclines. |
| Fuel selector/shutoff valve | Provides on the go switching from one tank to another giving the operator time to finish the mowing job and to return to the refueling source before the mower stops running. Both tanks can be shutoff with this valve for servicing and storage. |
| Molded-in dual cup holders and storage compartments | Tanks are molded with cup holders that fit a wide variety of cups and are in easy access to the driver. A storage compartment molded next to the cups offer additional operator convenience. |
| Lever activated park brake | A manually activated over-center park brake lever located next to the operator's left side for easy activation and release of automotive style drum brakes. Mower will not move until brake is released. |
| Hinged bayonet mount seat platform | Tilts up for easy access to battery and drive components or can be easily removed without tools. |
| Comfortable adjustable seat | Deluxe Cushion with/without spring suspension or Molded Vinyl with suspension and adjustable positioning for operator comfort and sustained productivity. |
| Seat safety interlocks | Rising off of the seat with blades engaged will cut engine power and stop blade rotation. Engine cannot be started with blade engagement switch in "on" position. |
| Hinged floor platform | Provides quick and convenient service access to topside deck components without tools. |
| Certified ROPS | Certified ROPS for added operator protection. |
| Sun Canopy | An optional folding soft sun canopy is available to fit fixed or folding ROPS. |
| Snow Plow | An optional 60" or 72" motion activated snow plow is available for snow removal and year round usage. Mower deck does not need to be removed to attach the snow plow. |
| EPA Compliant Mowers | |
| EPA approved six gallon fuel tanks with sight gauge, extra large tethered fuel caps and vent valve | 12 Gallon fuel capacity for plenty of operating range and decreased down time. Extra large fuel openings for easy fueling. Fuel caps are EPA approved, non vented, placed inboard and center mounted to protect caps from damage and prevent overflow spills on inclines. EPA vent valve help stops fuel leaks in rollover accidents and sight gauge makes it easy to see low fuel level in tanks. |
| Fuel tanks are vented to the engine carburetor | Engine burns fuel vapors instead of vapors leaking into the atmosphere. |

Designs, specifications, features and information are subject to change without notice.