

Features and Benefits

Zero Turn Mowers

ZT60i & ZT72i Accu-Z[®] (S/N 748110+)

Features	Benefits
60" or 72" cutting width	Sized right and priced right for ranch, estate owners, and commercial operators.
1" to 5" Cutting height	Provides a good range of cutting heights in 1/4' increments for any type of turf grass.
57 3/4" Outside drive tire stance	Provides excellent stability over uneven and hilly ground along with good maneuverability.
High ground speed	Forward 12 mph and reverse 6 mph for high productivity.
Adjustable steering levers with comfort grip handles	Wide range of adjustments to accommodate almost any size of operator. Grips are designed for operator comfort and sustained productivity.
Spring suspension seat platform	Helps smooth out the ride.
Strong deck design	New manufactured deck design has a great appearance on the outside, but tough parts on the inside. 3/16" Deck with 3/16" doubler plate, and a reinforced front edge.
Rapid deck height adjustment	The foot operated with spring assist deck lift and deck stop locator makes for a quick and easy precise cutting height adjustments.
Easy clean-out deck top	Deck allows air and debris move across the top for improved belt cooling and easy clean out.
Snap-on Deck Belt Guards	Deck belt guards can be hand removed easily without tools.
Excellent trim capability	Provides for good trim capability.
Mid-mount deck design	Puts deck closer to the operator's line of sight for more efficient and precise operation.
Floating deck design	Chain suspension design provides excellent flotation over uneven terrain.
Four anti-scalp rollers	Two located on deck ends and two located toward mid-decks keeps scalping to a minimum.
Completely independent twin hydrostatic drives	Separate expansion tanks eliminating the possibility of cross contamination.
Premium wide stance drive tires	Provide excellent traction, outstanding side-hill stability and a smooth ride. (24x12.00-12 4ply)
Front ribbed tires mounted in heavy duty pivoting caster forks	Provide for a quick and durable turning response. (13x6.5-6 ribbed tires)
Electric clutch control	Provides an easy smooth engagement of the mower blade drive system.
Kevlar drive belts	Drive belts made with Kevlar [™] fiber provide long belt life. One hydrostatic pump drive belt and one deck drive belt.
Stored wrench for assisting belt removal and installation	A wrench stored under the floor platform with 3/4" and 9/16" openings makes belt removal and replacement easy and possible without carrying extra wrenches.
1" blade spindles mounted in ductile iron housings	Additional 3/16" plate steel is added to the deck connecting the blade spindle housing mounts. Blade spindles, spindle housings and mounts are designed to handle heavy shock loads.
Accessible blade spindle zerks	Makes greasing the blade spindles easy.
Heavy duty heat treated Fusion [®] high lift blades	Made from highest quality .25" thick fusion treated steel for high wear and increase blade life. High lift design stands grass up before cutting.
High blade tip speed	Provides a clean quality cut. (60" deck = 18,350 fpm & 72" deck = 18,800 fpm)
Rear side mounted battery	Easy access to battery for servicing and maintaining.
Kawasaki engine	Proven engine to meet customer preferences with power and performance to spare.
Electric start with choke control	Keyed ignition and manual choke control are placed for one-handed starting convenience.
Engine oriented for easy access	Spark plugs, air filter, oil filter, & oil drain are placed easily within reach.
Center Mounted Rear Engine	Provides maximum mower stability, easy service access, increased leg room, and increased air flow around engine fins to extend engine life.
Remote Air Intake	All engines come standard with cyclonic type remote air intake to keep engines running clean and running longer.
Engine oil cooler	Keeps engine running at peak performance in warm weather conditions.
Isolated exhaust muffler	Muffler is hidden and tucked down under to reduce noise and provide protection against burns.
Ergonomically designed control console	Instrumentation and console controls are positioned for easy visual or fingertip access.
Hour meter	Measure actual engine run time to monitor service intervals.
Sleek styling EPA approved twin six gallon fuel tanks with sight gauge, extra large tethered fuel caps and vent valve	12 Gallon fuel capacity for plenty of operating range and decreased down time. Extra large fuel openings for easy fueling. Fuel caps are EPA approved, non vented, placed inboard and center mounted to protect caps from damage and prevent overflow spills on inclines. EPA vent valve help stops fuel leaks in rollover accidents and sight gauge makes it easy to see low fuel level in tanks.

Designs, specifications, features and information are subject to change without notice.

Features and Benefits

Zero Turn Mowers

ZT60i & ZT72i Accu-Z® (S/N 748110+)

Fuel tanks are vented to the engine carburetor	Engine burns fuel vapors instead of vapors leaking into the atmosphere.
Fuel selector/shutoff valve	Provides on the go switching from one tank to another giving the operator time to finish the mowing job and to return to the refueling source before the mower stops running. Both tanks can be shutoff with this valve for servicing and storage.
Molded-in dual cup holders and storage compartments	Tanks are molded with cup holders that fit a wide variety of cups and are in easy access to the driver. A storage compartment molded next to the cups offer additional operator convenience.
Lever activated park brake	A manually activated over-center park brake lever located next to the operator's left side for easy activation and release of internal wet disk brakes. Mower will not move until brake is released.
Hinged bayonet mount seat platform	Tilts up for easy access to battery and drive components.
Comfortable adjustable seat	Deluxe Cushion or Molded Vinyl with suspension and adjustable positioning for operator comfort and sustained productivity.
Seat safety interlocks	Rising off of the seat with blades engaged will cut engine power and stop blade rotation. Engine cannot be started with blade engagement switch in "on" position.
Hinged floor platform	Provides quick and convenient service access to topside deck components without tools.
Certified ROPS	Certified ROPS for added operator protection.