

ZT360 & ZT372 Models

Features	Benefits
Cutting width of 60" or 72"	Sized right and priced right for ranch, estate owners, and commercial operators.
Cutting height of 1" to 5"	Provides a good range of cutting heights in 1/4" increments for any type of turf grass.
ZT360 = 52" & ZT372 = 56" Outside drive tire stance	Provides excellent stability over uneven and hilly ground along with good maneuverability. ZT360 is also available, as an option, with 56" outside drive tire stance.
High ground speed	Forward 12 mph and reverse 6 mph for high productivity.
Adjustable steering levers with comfort grip handles	Wide range of adjustments to accommodate almost any size of operator. Grips are designed for operator comfort and sustained productivity.
Spring suspension seat platform	Helps smooth out the ride.
Strong deck design	New manufactured deck design has a great appearance on the outside, but tough parts on the inside. 3/16" Deck with 1/4" doubler plate, and a reinforced front edge.
Rapid deck height adjustment	The foot operated with spring assist deck lift and deck stop locator make for quick and easy precise cutting height adjustments.
Easy clean-out deck top	Deck allows air & debris to move across the top for improved belt cooling & easy clean out.
Snap-on deck belt guards	Deck belt guards can be hand removed easily without tools.
Excellent trim capability	Provides for good trim capability.
Mid-mount deck design	Puts deck closer to the operator's line of sight for more efficient and precise operation.
Floating deck design	Chain suspension design provides excellent flotation over uneven terrain.
Four anti-scalp rollers	Two located on deck ends and two located toward mid-deck keeps scalping to a minimum.
Completely independent twin hydrostatic drives	Separate expansion tanks eliminate the possibility of cross contamination.
Premium wide stance drive tires	Provide excellent traction, outstanding side-hill stability and a smooth ride.
Ribbed front tires mounted in heavy duty pivoting caster forks	Provide for a quick and reliable turning response.
Tele-Caster® wheel spindles	Spring loaded caster wheel spindles for superior shock absorption over rough terrain.
Lockable floating front axle	Floating front axle provides for smoother ride and optimal traction capability by keeping all tires equally in contact with the ground over uneven terrain. Locking front axle provides for a more uniform cut and curb or edge cutting without grounding or hanging up the deck.
Electric clutch control	Provides an easy smooth engagement of the mower blade drive system.
Kevlar drive belts	Drive belts made with Kevlar™ fiber provide long belt life. One hydrostatic pump drive belt and one deck drive belt.
1" blade spindles mounted in ductile iron housings	Additional 3/16" plate steel is added to the deck connecting the blade spindle housing mounts. Blade spindles, spindle housings and mounts are designed to handle heavy shock loads.
Accessible blade spindle zerks	Makes greasing the blade spindles easy.
Heavy duty heat treated Fusion® high lift blades	Made from highest quality .25" thick fusion treated steel for high wear and increase blade life. High lift design stands grass up before cutting.
High blade tip speed	Provides a clean quality cut. See specifications for actual speeds.
Battery located under the seat	Easy access to battery for servicing and maintaining.
Kawasaki engine	Proven engine to meet customer preferences with power and performance to spare.
Electric start with choke control	Keyed ignition and manual choke control are placed for one-handed starting convenience.
Engine oriented for easy access	Spark plugs, air filter, oil filter, & oil drain are placed easily within reach.
Center Mounted Rear Engine	Provides maximum mower stability, easy service access, increased leg room, and increased air flow around engine fins to extend engine life.
Remote Air Intake	All engines come standard with cyclonic type remote air intake to keep engines running clean and running longer.
Engine oil cooler	Keeps engine running at peak performance in warm weather conditions.

ZT360 & ZT372 Models

Features	Benefits
Isolated exhaust muffler	Muffler is hidden and tucked down under to reduce noise and provide protection against burns.
Ergonomically designed control console	Instrumentation and console controls are positioned for easy visual or fingertip access.
Hour meter	Measure actual engine run time to monitor service intervals.
Sleek styling EPA approved twin six gallon fuel tanks with sight gauge, extra large tethered fuel caps and vent valve	12 Gallon fuel capacity for plenty of operating range and decreased downtime. Extra large fuel openings for easy fueling. Fuel caps are EPA approved, non vented, placed inboard and center mounted to protect caps from damage and prevent overflow spills on inclines. EPA vent valve helps stop fuel leaks in rollover accidents and sight gauge makes it easy to see low fuel level in tanks.
Fuel tanks are vented to the engine carburetor	Engine burns fuel vapors instead of vapors leaking into the atmosphere.
Fuel selector/shutoff valve	Provides on-the-go switching from one tank to another giving the operator time to finish the mowing job and to return to the refueling source before the mower stops running. Both tanks can be shutoff with this valve for servicing and storage.
Molded-in dual cup holders and storage compartments	Tanks are molded with cup holders that fit a wide variety of cups and are in easy access to the driver. A storage compartment molded next to the cups offer additional operator convenience.
Lever activated park brake	A manually activated over-center park brake lever located next to the operator's left side for easy activation and release of internal wet disk brakes. Mower will not move until brake is released.
Hinged seat platform	Tilts up for easy access to battery and drive components.
Comfortable adjustable seat	Deluxe Cushion or Molded Vinyl with suspension and adjustable positioning for operator comfort and sustained productivity.
Seat safety interlocks	Rising off of the seat with blades engaged will cut engine power and stop blade rotation. Engine cannot be started with blade engagement switch in "on" position.
Hinged floor pan	Provides quick and convenient service access to topside deck components without tools.
Certified ROPS	Certified ROPS for added operator protection.
All Steel Pulleys	Steel pulleys last longer.