

Rotary Tillers, Standard Tine Rotation

RTA10 Series			
	RTA1042	RTA1050	RTA1058
Width	42"	50"	58"
Overall Width	47 5/16"	55 5/16"	63 5/16"
Weight	358#	385#	415#
Number of flanges	5	6	7
Number of Tines per Flange			
Driveline	Category II Shear bolt - standard Slip Clutch - optional		
Gearbox	25 HP input at 540rpm 1.5:1 ratio Cast iron housing, straight bevel gears		
Gearbox Lubrication	Gear Lube 80-90W EP		
Drive Chain	#80 roller chain in flowable grease bath		
Drive Chain Lubrication	Shell Alvania EP 00 or equivalent		
Sprockets	Case hardened teeth, splined bores		
Rotor Swing Diameter	15"		
Rotor Shaft Speed	225 rpm at 540 rpm PTO		
Recommended Maximum PTO HP	25 HP		
Hitch Type	Category I, offsetable, works with Land Pride Quick-Hitch (Note: Cannot be offset when using the Quick-Hitch)		

RTA15 Series		
	RTA1550	RTA1558
Width	50"	58"
Overall Width	56 1/4"	64 1/4"
Weight	412#	444#
Number of Flanges	6	7
Number of Tines per Flange	4	
Driveline	Category III Heavy Duty Shear bolt - standard Friction Clutch - optional	
Gearbox	35 HP input at 540 rpm 1.92:1 ratio Cast iron housing, straight bevel gears	
Gearbox Lubrication	Gear Lube 80-90W EP	
Drive Chain	#80 roller chain in flowable grease bath	
Drive Chain Lubrication	Shell Alvania EP 00 or equivalent	
Sprockets	Case hardened teeth, splined bores	
Rotor Swing Diameter	15"	
Rotor Shaft Speed	211 rpm at 540 rpm PTO	
Recommended Maximum PTO HP	35 HP	
Hitch Type	Category I, Sideshift capabilities, works with Land Pride Quick-Hitch (Note: Sideshift capabilities also works with Land Pride Quick-Hitch)	

Designs, specifications, features and information are subject to change without notice.