

Single Deck Rotary Cutters

RCR15 Series				
	RCR1542	RCR1548	RCR1560	RCR1572
Hitch	Category I			
Working Width	42"	45 1/2"	57"	69"
Overall Width	47 1/2"	50"	62"	74"
Overall Length (Including Tailwheel)	86"	90"	96"	108"
Machine Weight (with Front Guard)	432#	475#	495#	614#
Blade Tip Speed	11,459 fpm	13,090 fpm	16,363 fpm	14,874 fpm
Deck Material Thickness	12 Gauge			
Gearbox Rating	30 HP		40 HP	
Horsepower Rating	15-50		20-50	25-50
Cutting Height	1 3/4" - 11 1/2"		1" - 9"	1" - 9"
Cutting Capacity	Grass			
Safety Guards	Rubber (front) or Chain (front or rear)			
Skids	1/4" X 2" Weld on			
Deck Height (Bottom of Deck to Bottom of Skid Shoe)	7 1/4"			
Blades	1/2" x 3" Heat Treated Alloy Steel Free-Swinging Blades			
Stump Jumper	Round Pan 10 ga. x 24"	Round Pan 10 ga. x 24"	Round Pan 10 ga. x 24"	Round Pan 10 ga. x 24"
Driveline	ASAE Category 3			
Driveline Safety Protection	Standard 1/2" Center Shearbolt protection Optional - Center Bolt 2 plate Slip Clutch			
Gearbox (Speed up beveled gears)	540 rpm PTO Driven Gearbox 1:1.93 Cast Iron Housing	540 rpm PTO Driven Gearbox 1:1.47 Cast Iron Housing		
Tailwheel	4" x 8" x 15" Laminated Tire, cast iron hub Optional - 4" x 16" Solid Rubber Tire			

Designs, specifications, features and information are subject to change without notice.