

Rotary Cutters, Single Deck

RCR2660 and RCR2672 Models		
	RCR2660	RCR2672
Cutting Width	60"	72"
Overall Width	67"	79"
Overall Length (Including Tailwheel)	114"	126"
Blade Tip Speed	12,384 fpm/788 rpm	14,861 fpm/788rpm
Machine Weight (with Chain Guards)	1,002#	1,046#
Driveline	ASAE Category 4	
Slip Protection	4 Plate Slip Clutch	
Recommended Tractor HP	40-110 maximum	
PTO Speed	540 rpm	
Gearbox	540 rpm PTO Driven Gearbox 1:1.46 Speed-Up Beveled Gears Cast Iron Housing	
Gearbox Lubrication	80-90W EP oil	
Gearbox Output Shaft	2" dia.	
Cutting Height	2" - 12"	
Deck Material Thickness	10 Gauge	
Side Panel Thickness	1/4"	
Deck Height	9 1/8" (Bottom of Deck to Bottom of Skid Shoe)	
Deck Construction	All welded construction	
Skids	Replaceable	
Tailwheel Mount Assembly	Welded arm and Caster Fork	
Tailwheel	4.00 x 8 x 15 Laminated Tire with cast iron hub and tapered roller bearings	
Hitch	Category I or II	
Stump Jumper	Round Pan 3/16" x 25"	Round Pan 3/16" x 32"
Blades (2)	1/2" x 4" x 25" Heat Treated Alloy Steel Free-Swinging High Lift	1/2" x 4" x 29" Heat Treated Alloy Steel Free-Swinging High Lift
Blade Bolt	Keyed with harden flat washer and lock nut	
Blade Cutting Capacity	2"	
Front Guard	Chain Guard - Standard Rubber Guard - Available through Parts Department	
Rear Guard	Chain Guard - Standard	

Designs, specifications, features and information are subject to change without notice.