

## Specifications & Capacities

### Rotary Cutters, Single Deck

<b>RCR2684 Model</b>	
	<b>RCR2684</b>
<b>Cutting Width</b>	84"
<b>Overall Width</b>	90 3/4"
<b>Overall Length (Including Tailwheel)</b>	Single Tailwheel 133" Dual Tailwheel 116"
<b>Blade Tip Speed</b>	540 RPM PTO: 14,369 FPM / 163 MPH
<b>Machine Weight</b>	Single Tailwheel 1370# Dual Tailwheel 1500#
<b>Driveline</b>	ASAE Category 4
<b>Slip Protection</b>	4 Plate Slip Clutch
<b>Recommended Tractor HP</b>	60 to 110 HP
<b>PTO Speed</b>	540 rpm
<b>Gearbox</b>	540 RPM PTO Driven 1 3/8" 6-Spline Input Shaft Beveled Gears in Cast Iron Housing
<b>Gearbox Lubrication</b>	80-90W EP oil
<b>Gear box Output Shaft Diameter</b>	2"
<b>Cutting Height</b>	2" - 12"
<b>Deck Material Thickness</b>	10 Gauge
<b>Side Panel Thickness</b>	1/4"
<b>Deck Height</b>	10 1/8" Bottom of deck to bottom of skid.
<b>Deck Construction</b>	All Welded
<b>Skids</b>	Replaceable
<b>Tailwheel Mount Assembly</b>	Welded Arm and Caster Fork.
<b>Tailwheel(s)</b>	Provided with single or dual tailwheels. 4.00 x 8 x 15 1/4 Laminated Tire(s) with Cast Iron Hub and Tapered Roller Bearings.
<b>Hitch</b>	Category II Standard & Category III Adaptable
<b>Stump Jumper</b>	Oval Pan 3/16" x 24" x 38"
<b>Blades (2)</b>	1/2" x 4" x 31" Heat Treated Alloy Steel Free-Swinging High Suction Blades
<b>Blade Bolts</b>	Keyed with Harden Flat Washer and Lock Nut
<b>Blade Cutting Capacity</b>	2"
<b>Optional Front Guard</b>	Chain guard - Standard Rubber guard - Available through parts department.
<b>Optional Rear Guard</b>	Chain guard - Standard

*Designs, specifications, features and information are subject to change without notice.*