

Primary Seeders

PS1548 & PS1572 Primary Seeders		
	PS1548	PS1572
Width	55"	72"
Seeding Width (Broadcast)	51"	70 1/2"
Weight (Approximate Pounds)	870#	1165#
Seed Capacity	1 Bushel/Foot (4 bushel)	1 Bushel/Foot (6 bushel)
Feeder Cup Drive (Roller Drive)	Chain Driven from right side of front roller with paddle type agitator above seed cups	Chain Driven from right side of front roller with paddle type agitator above seed cups
Track Removers	Double torsion spring height adjustable and replaceable One each	Double torsion spring height adjustable and replaceable Two each
Bed Forming Rollers - Front	12" OD notched, cast iron, 20 each with free floating mounting tube and 1 1/2" sealed greaseable bearings	12" OD notched, cast iron, 29 each with free floating mounting tube and 1 1/2" sealed greaseable bearings
Bed Forming Rollers - Rear	9 1/2" OD notched, cast iron, 21 each with free floating mounting tube and 1" greaseable bearing mounted on pivoting spring loaded arms	9 1/2" OD notched, cast iron, 28 each with free floating mounting tube and 1" greaseable bearing mounted on pivoting spring loaded arms
Hitch	Category I, Offset to right 8 5/8"	Category I