

**Post Hole Diggers**

<b>HD25 and HD35 Series Hydraulic Post Hole Diggers</b>				
	<b>HD25 (3-Point)</b>	<b>HD25 (Bucket Mount)</b>	<b>HD35 (3- Point)</b>	<b>HD35 (Bucket Mount)</b>
<b>Hitch</b>	Cat I or II	Bucket Mount	Cat I or II	Bucket Mount
<b>Yoke</b>	2 7/8" Tubing	Not Applicable	2 7/8" Tubing	Not Applicable
<b>Boom</b>	Reinforced Tubing	Not Applicable	Reinforced Tubing	Not Applicable
<b>Hydraulic Hoses</b>	Standard	Optional	Standard	Optional
<b>Maximum Auger RPM</b>	109 RPM	105 RPM	109 RPM	105 RPM
<b>Gallons Per Minute Rating</b>	5 -12 GPM @ 1500 to 3000 PSI		10 -25 GPM @ 1500 to 3000 PSI	
<b>Max torque @ 2500 PSI</b>	700 ft. lbs.		1605 ft. lbs.	
<b>Gearbox</b>	3.18:1 Ratio			
<b>Output Shaft on Gearbox</b>	2"			
<b>Driveline</b>	Hydraulic			
<b>Auger Pipe</b>	2 1/2" dia.			
<b>Auger Flighting Thickness</b>	1/4"			
<b>Auger Length</b>	48"			
<b>Auger Sizes</b>	6", 9", 12", 15", 18" or 24"			
<b>Auger Teeth</b>	Forged, Individually Replaceable 40 Degree Angle Installed on Flat Side 50 Degree Angle Installed on Angled Side			
<b>Number of Teeth</b>	(6" - 2 teeth) (9" & 12" - 4 teeth) (15" - 5 teeth) (18" - 6 teeth) (24" - 8 teeth)			
<b>Machine Weight with 6" Auger</b>	235 lbs.	185 lbs.	235 lbs.	189 lbs.
<b>Optional Hydraulic Hoses</b>	Not Applicable	(2)-24 ft. long hoses	Not Applicable	(2)-24 ft. long hoses
<b>Optional Hydraulic Down Pressure Kit</b>	Available	Not Applicable	Available	Not Applicable
<b>Optional Storage Stand</b>	Available	Not Applicable	Available	Not Applicable
<b>Auger Extension Accessories</b>	7" and 14" Extensions Available			