

## Specifications & Capacities

### Rotary Cutters, Folding Deck

#### RCR3515 and RCRM3515 Models

	RCR3515 & RCRM3515
Cutting Width	15'
Overall Width	15'-8"
Minimum Transport Width	8'
Cutting Height	2" - 14"
Overall Length	15'-1"
Deck Material Thickness	10 gauge
Deck Height	9"
Debris Guards	Single Row Chain or Rubber
Hitch Type	Pull, Self - Leveling Hitch & Clevis
Blades - 6 (2 per Carrier)	1/2" x 4" Heat Treated Free Swinging Alloy Steel with Uplift
Blade Tip Speed	(540 rpm = 15,268 fpm center & 15,000 fpm wings) (1,000 rpm = 15,578 fpm center & 14,620 fpm wings)
Blade Holders	Round Pan
PTO Drive Shafts	540 PTO: ASAE Category 4 {Input Shafts} 1000 PTO ASAE Category 4 {Output Shafts}
Connecting Drivelines	Standard - Category 4 with Slip-Clutch Optional - Category 5 with Slip-Clutch
Gear Boxes	540 RPM or 1000 RPM 160 HP Divider 110 HP Center & Wings
Wheel Options	6" x 21" Laminated or 15" Rims or 27"5 x 7.75" x 15" Used Aircraft Tires
Shock Load Suspension	Springs on center axle
Machine Weight	3,780 lbs.
Tongue Weight	1300 lbs.
Min. PTO Horse Power	50

*Designs, specifications, features and information are subject to change without notice.*