

Vehicles, Treker

4200NT, 4200ST, 4400NT & 4400ST Series

Engine	Honda GX620K1	Body Cowling	ABS Composite
Engine Type	4 stroke - air cooled	Floorboards	Steel Safety Plate
Horse Power	20	Frame Construction	Tube & Channel
Displacement	614 cc	Frame. Suspension	Independent A-arms MacPherson Struts
Cylinders	2	Rear Suspension	Independent trailing arms Coil/over Adjustable Shocks
Valving	OHV	Fenders	Front: Integral Rear: Bed Mounted
Lubrication	Pressurized	Front Bumper	Optional
Engine Oil Type	SAE 10W30	Front Brush Guard	Optional
Engine Oil Capacity	1.5 US qts. with filter change 1.1 US qts. without filter change	Seating	Buckets - 2
Engine Idle rpm	1250 rpm min. to 1350 rpm max.	4-Post Acc.Bar	Standard
Max. Engine Static rpm	3800 rpm to 4000 rpm max.	Rear Hitch	2" receiver
Max. Torque	32.5 lb@2500	Approximate Curb Weight	4200NT: 860 lbs. 4200ST: 925 lbs. 4400NT: 985 lbs. 4400ST: 1050 lbs.
Cooling	Air	Base Unit Total Payload*	NT: 950 lbs. ST: 1300 lbs.
ACG Output	12V/20A	Gross Vehicle Weight	4200NT: 1810 lbs. 4200ST: 2225 lbs. 4400NT: 1935 lbs. 4400ST: 2350 lbs.
Ignition	Keyed	Rear Cargo Box Capacity	NT: 550 lbs. ST: 950 lbs.
Battery	300 cca	Maximum Tongue Weight	100 lbs.
Spark Arrestor	Standard	Max. Towing Capacity	1200 lbs.
Headlights	Standard	Wheel Base	NT: 70" ST: 76"
Tail Lights	Standard	Tread Center Front	NT: 41.5" ST: 46.5"
Fuel Capacity	NT: 4 gallon ST: 8 gallon	Tread Center Rear	NT: 42" ST: 47.5"
Fuel Type	Unleaded fuel with 87 min. octane (Methanol fuel not allowed)	Width at front tires	NT: 50" ST: 54"
Rear Trans-axle Case Oil Capacity and Type	20 oz. US 80/90 Gear Lube	Width at rear tires	NT: 50.5" ST: 58"
Center Transfer Case Oil Capacity and Type	6 oz. US 80/90 Gear Lube	Height	With AT Tires: 71" With Turf Tires: 70"
Front Differential Case Oil Capacity and Type	5 oz. Land Pride Special Formulated Gear Lube	Length	NT: 108" ST: 120"
Trans-axle	Shielded CVT (Constantly Variable Transmission)	Floorboard Height	AT Tires: 14" Turf Tires: 13"
Gear Selection	Forward/Neutral/Reverse with Neutral Start	Min. Ground Clearance	9 1/2"
Max. Speed	25 mph	Tire Size (Front)	25x8-12 All-Terrain Tread 23x8.5-12 Turf
Brakes	Front: Hydraulic Disc Rear: Hydraulic Drum	Tire Size (Rear)	25x11-12 All-Terrain Tread 23x10.5-12 Turf
Brake oil	DOT 3	Tire Pressure (Front)	7 psi
Steering	Rack & Pinion	Tire Pressure (Rear)	7 psi**
Steering Wheel Dia.	15"	Optional Front Cargo Rack Capacity	160 lbs.

* Base unit does not include optional cargo racks.

** Tire pressure may be increased to accommodate additional cargo load. Max.tire pressure is noted on tire side wall.

Designs, specifications, features and information are subject to change without notice.

Vehicles, Treker

4210ST & 4410ST Series

Engine	Honda GX620K1	Floorboards	Steel Safety Plate
Engine Type	4 stroke - air cooled	Frame Construction	Tube & Channel
Horse Power	20	Frame. Suspension	Independent A-arms MacPherson Struts
Displacement	614 cc	Rear Suspension	Independent trailing arms Coil/over Adjustable Shocks
Cylinders	2	Fenders	Front: Integral Rear: Bed Mounted
Valving	OHV	Front Bumper	Standard
Lubrication	Pressurized	Front Brush Guard	Optional
Engine Oil Type	SAE 10W30	Seating	2- Bucket seats or 1- Bench Seat
Engine Oil Capacity	1.5 US qts. with filter change 1.1 US qts. without filter change	Seat Belts	2- Standard with an optional 3rd Belt
Engine Idle rpm	1250 rpm min. to 1350 rpm max.	4-Post Acc.Bar	Standard
Max. Engine Static rpm	3800 rpm to 4000 rpm max.	Rear Hitch	2" receiver
Max. Torque	32.5 lb@2500	Front Hitch	2" receiver available with front Brush Guard option
Cooling	Air	Approximate Curb Weight	4210ST: 925 lbs. 4410ST: 1234 lbs.
ACG Output	12V/20A	Base Unit Total Payload*	1300 lbs.
Ignition	Keyed	Gross Vehicle Weight	4210ST: 2225 lbs. 4410ST: 2534 lbs.
Battery	300 cca	Rear Cargo Box Capacity	950 lbs.
Spark Arrestor	Standard	Maximum Tongue Weight	100 lbs.
Headlights	Standard	Max. Towing Capacity	1200 lbs.
Tail Lights	Standard	Wheel Base	76"
Fuel Capacity	8 gallon	Tread Center Front	46.5"
Fuel Type	Unleaded fuel with 87 min. octane (Methanol fuel not allowed)	Tread Center Rear	47.5"
Rear Trans-axle Case Oil Capacity and Type	20 oz. US Mobil 424	Width at front tires	54"
Center Transfer Case Oil Capacity and Type	6 oz. US 80/90 Gear Lube	Width at rear tires	58"
Front Differential Case Oil Capacity and Type	5 oz. US Mobil 424	Height	With AT Tires: 71" With Turf Tires: 70"
Trans-axle	Enclosed CVT (Constantly Variable Transmission)	Length	120"
Gear Selection	Park/Neutral/Forward/Reverse with Park/Neutral Start & Integral Park Brake	Floorboard Height	AT Tires: 14" Turf Tires: 13"
Max. Speed	25 mph	Min. Ground Clearance	9 1/2"
Brakes	Front: Hydraulic Disc Rear: Hydraulic Drum	Tire Size (Front)	25x8-12 All-Terrain Tread 23x8.5-12 Turf
Brake oil	DOT 3	Tire Size (Rear)	25x11-12 All-Terrain Tread 23x10.5-12 Turf
Steering	Rack & Pinion	Tire Pressure (Front)	7 psi
Steering Wheel Dia.	15"	Tire Pressure (Rear)	7 psi**
Body Cowling	ABS Composite	Optional Front Cargo Rack Capacity	160 lbs.

* Base unit does not include optional cargo racks.

Designs, specifications, features and information are subject to change without notice.