

**Vehicles, Treker**

**4220ST & 4420 ST Series**

<b>Engine Specifications</b>			
<b>Engine Model</b>	Honda GX620K1	<b>Lubrication</b>	Pressurized
<b>Engine Type</b>	4 stroke - air cooled	<b>Engine Oil Type</b>	SAE 10W30
<b>Horse Power</b>	20	<b>Engine Oil Capacity</b>	1.5 US qts. with filter change 1.1 US qts. without filter change
<b>Displacement</b>	614 cc	<b>Engine Idle rpm</b>	1250 rpm min. to 1350 rpm max.
<b>Max. Torque</b>	32.5 lb@2500	<b>Max. Engine Static rpm</b>	3800 rpm to 4000 rpm max.
<b>Cylinders</b>	2	<b>Cooling</b>	Air
<b>Valving</b>	OHV	<b>ACG Output</b>	12V/20A
<b>Fuel And Oil Specifications</b>			
<b>Fuel Capacity</b>	8 gallons	<b>Rear Trans-axle Case</b>	Capacity: 20 oz. Type: US Mobil 424
<b>Fuel Type</b>	Unleaded fuel with 87 min. octane (Methanol fuel not allowed)	<b>Center Transfer Case</b>	Capacity: 6 oz. Type: US 80/90 gear lube
<b>Brake Fluid</b>	DOT 3	<b>Front Differential Case</b>	Capacity: 5 oz. Type: US Mobil 424
<b>Vehicle Specifications</b>			
<b>Headlights</b>	Two with standard 37.5 watt bulbs #894	<b>4-Post Acc.Bar</b>	Standard
<b>Tail Lights</b>	Two with standard bulbs #1157	<b>Max. Speed</b>	25 mph
<b>Battery Type</b>	12 volt, Size BCI, Group U1/U1R with min. 300 CCA and 375 CCA at 32°F.	<b>Approximate Curb Weight</b>	4220ST: 925 lbs. 4420ST: 1234 lbs.
<b>Back-up Light/Alarm</b>	Available as accessories	<b>Base Unit Total Payload*</b>	1300 lbs.
<b>Belt Drive</b>	Enclosed CVT (Constantly Variable Transmission)	<b>Gross Vehicle Weight</b>	4220ST: 2225 lbs. 4420ST: 2534 lbs.
<b>Ignition</b>	Keyed (Starts only in park and neutral.)	<b>Rear Cargo Box Capacity</b>	900 lbs.
<b>Gear Selection</b>	Park/Neutral/Forward/Reverse	<b>Maximum Tongue Weight</b>	100 lbs.
<b>Rear Park Brake Operator</b>	Gear selector automatically sets rear brakes when placed in park.	<b>Max. Towing Capacity</b>	1200 lbs.
<b>Brake Type</b>	Front: Hydraulic disc Rear: Hydraulic drum	<b>Carrying Capacity of Front Optional Cargo Rack</b>	160 lbs.
<b>Steering Type</b>	Rack & Pinion	<b>Wheel Base</b>	76"
<b>Steering Wheel Dia.</b>	15"	<b>Tread Center Front</b>	46.5"
<b>Exhaust Protection</b>	Spark arrestor	<b>Tread Center Rear</b>	47.5"
<b>Frame Construction</b>	Tube & channel	<b>Width at front tires</b>	54"
<b>Frame. Suspension</b>	Independent A-arms, MacPherson struts	<b>Width at rear tires</b>	58"
<b>Rear Suspension</b>	Independent trailing arms Coil/over adjustable shocks	<b>Height</b>	With All-Terrain tires: 71" With Turf tires: 70"
<b>Floorboards</b>	Steel safety plate	<b>Length</b>	120"
<b>Body Cowling</b>	ABS Composite in optional colors: Green, Red, Yellow or Camouflage	<b>Floorboard Height</b>	All-Terrain tires: 14" Turf tires: 13"
<b>Front Guard</b>	Optional bumper or brush guard	<b>Min. Ground Clearance</b>	9 1/2"
<b>Rear Hitch</b>	2" receiver	<b>Tire Pressure</b>	Front & Rear = 7 psi**
<b>Front Hitch</b>	2" receiver available with front brush guard option	<b>Tire Type &amp; Size (Front)</b>	All-Terrain tread with black or gray rims: 25 x 8-12 (option) Turf tread: 23 x 8.5-12 (option)
<b>Fenders</b>	Front: Integral with body Rear: Mounted to cargobox	<b>Tire Type &amp; Size (Rear)</b>	All-Terrain tread with black or gray rims: 25 x 11-12 (option) Turf tread: 23x10.5-12 (option)
<b>Seating</b>	Bench seat with two seat belts. Center 3rd seat belt available as an accessory.		

\* Base unit does not include optional cargo racks.

\*\* Tire pressure may be increased to accommodate additional cargo load. Max.tire pressure is noted on tire side wall.

**Designs, specifications, features and information are subject to change without notice.**