



- Hitch: Cat. 2 or 3 (Quick Hitch Adaptable)
- Hydraulic Adjustments with Cylinders & Hoses
- Hydraulic Hose Storage
- Main Frame: Fully Enclosed Formed Box
- Retractable Parking Stand
- Options: Gauge Wheels, End Panels, Skid Shoes

	RBT6010	RBT6012
Hitch	Cat. 2 or 3 (Quick Hitch Adaptable)	
Working Width	10'	12'
Max Tractor HP Range	2 Wheel Drive: 10' - 225 HP 12' - 175 HP 4 Wheel Drive: 10' - 200 HP 12' - 160 HP	
Blade Angles	up to 45 Degrees, Forward & Reverse, 4 $\frac{1}{2}$ " x 16" Cylinder	
Offset	Up to 55" Left & Right, 4 $\frac{1}{2}$ " x 16" Cylinder	
Tilt	Up to 30 Degrees, 3 $\frac{1}{2}$ " x 8" Cylinder	
Moldboard	19" Tall, $\frac{1}{2}$ " Thick w/Reinforcement Channel	
Kingpin	4 $\frac{1}{2}$ " Solid Steel Bar	
Cutting Edge	$\frac{1}{2}$ " x 6" Heat Treated	