

Rotary Cutters: 36 Series

Medium Duty



- **2 1/2" Cutting capacity**
- **Low tongue weight is ideal for smaller HP tractors by reducing the amount of weight on the drawbar**
- **Smooth top design allows for quick and easy cleaning of deck**
- **6" Blade overlap eliminates skipping during turns**



	RC3615
Working Width	15'
Transport Width	8' Minimum
Overall Width	15'8"
Overall Length	15'1"
Hitch	Pull-Type, Self-Leveling Hitch & Clevis
Cutting Height	2" - 14"
Deck Height	9"
Deck Thickness	10 Gauge
Side Skirt Thickness	1/4"
Gearbox	540 rpm: 160 HP Divider; 110 HP Center & Wings; 1000 rpm: 160 HP Divider; 110 HP Center & Wings
Gearbox Input Shaft	1 3/4" 20 Spline
Gearbox Output Shaft	2"
Input Driveline	Constant Velocity U-Joint or Conventional; Cat. 5
Connecting Driveline	Cat. 4 Slip-Clutch
Stump-Jumper	3/16", Round, Dish Shaped
Blades	2 per Section, 1/2" x 4" Heat Treated; Free Swinging Alloy Steel with Uplift
Blade Speed	540 rpm: Center: 15,268 fpm, Wings: 15,000 fpm 1000 rpm: Center: 15,578 fpm, Wings: 14,620 fpm
Skid Shoes	Wings & Center, Replaceable
Front and Rear Shielding	Optional Single or Double Chain, or Rubber
Side Skirt Thickness	1/4"
Wheel Options	4, 6 or 8 Wheels, with Spring-Cushioned Center Axle 6" x 21" Laminated Tires 24" x 7.75" x 15" Used Aircraft Tires w/wo foam
Wing Hydraulics	2 1/2" x 12" Cylinder, Hoses & Fittings
Height Adjustments	3" x 8" Cylinder, Hose, Fittings & Stroke Control Spacers