

POWERED DITCHER



The DT55 Powered Ditcher is a versatile tool to use in many water control applications. Cleaning water ditches along roadsides or in farm fields to drain standing water away from crops, the DT55 Ditcher makes it simple. The 20" impeller leaves a clean and sculptured trough to keep water flowing freely from unwanted areas. With the Material Control Chute in place, dirt can be placed just next to the machine, or thrown many feet away to reshape terraces.



DT55 SERIES

70 - 200 HP — Powered Ditcher

- Lubricated chain drive
- Dual parking stands for storage stability
- Optional rear skid shoe helps control depth
- Optional material chute puts dirt where you want it
- Optional ripper shank tears through hard packed soils moving smaller material into the impeller path
- Optional gauge wheel for depth control

Powered Ditcher Specifications

Model Number	DT55	DTM55
Tractor PTO	540 rpm	1000 rpm
Hitch*	Cat. 2 & 3, QH adaptable (*Some early models not QH adaptable)	
HP Range	70 – 200 HP	
Weight (kg)	900 lbs. (408) (without options)	
Impeller	20" Impeller	
Impeller Blades	6 ea, 3/8" Thick steel with replaceable hardened cutting edges	
Chain	Double 80 chain with spring loaded idler	
Input/Output Shafts	2-1/4" ID ball type bearings	
Driveline	Cat. 5 with shear-bolt	
Material Control Chute (Optional)	Manual or with 2" x 8" hydraulic cylinder and hoses	
Depth Control Wheel (Optional)	16.5 x 6.50-8 Pneumatic tire Adjustable from cutting edge height to 10" below	
Ripper Shank (Optional)	3 Height adjustments Cutting edge depth to 5" below	
Skid Shoe (Optional)	3/8" thick, replaceable	

Models may or may not include options.
Design and specifications subject to change without notice.