

POST HOLE DIGGERS

HD25 SERIES

5 - 12 GPM — 6" - 24" Augers

The hydraulic driven bucket mount Post Hole Digger is easily bolted to the side of your front end loader bucket. The hydraulics on the bucket can be used as additional force in digging through heavy soil. Available in HD25 or HD35 Series.

5 year
Limited
Gearbox Warranty*



HD35 SERIES

10 - 25 GPM — 6" - 24" Augers

The hydraulic driven, 3-point tractor mounted Post Hole Digger uses the tractor hydraulics to turn the auger; no driveline to hassle with! You can also reverse the auger direction, easing the strain on the auger when extracting it from the ground. Available in HD25 or HD35 Series.

5 year
Limited
Gearbox Warranty*



SA35 SERIES

Skid Steer
15 - 25 GPM

- 2" Hex or 2-9/16" output shaft
- Use skid steer to push auger into ground
- 9", 12", 15", 18", 24", 30", 36" Double flight auger
- 24", 30", & 36" Tree augers
- 24" & 48" Auger extensions

5 year
Limited
Gearbox Warranty*

Post Hole Digger Specifications

Model Number	PD10	PD15	PD25/PD35	HD25/35	SA35
Hitch	Category I	Category I	Category I or II	Cat. I or II, or bucket mount	Skid Steer Plate
Yoke (cm)	2-7/8" (7.30) Tubing	2-7/8" (7.30) Tubing	2-7/8" (7.30) Tubing	2-7/8" (7.30) Tubing	2-7/8" (7.30) Tubing
Boom (cm)	2-7/8" (7.30) Tubing	2-7/8" (7.30) Tubing	3-1/2" (8.89) Reinforced Tubing	3-1/2" (8.89) Reinforced Tubing	3-1/2" (8.89) Reinforced Tubing
Gearbox	30 HP max	40 HP max	55 HP max/75 HP max	3:18:1	
GPM rating	N/A	N/A	N/A	HD25: 5-12 GPM HD35: 10-25 GPM	SA35: 15-25 GPM
Output Shaft (cm)	2" (5.08)	2" (5.08)	2" (5.08)	2" (5.08)	2" Hex or 2-9/16" OD
Input RPM	540 Tractor at 300 RPM	540 Tractor at 300 RPM	540 Tractor at 300 RPM		
Driveline	Category 2	Category 2	Category 3	Hydraulic	Hydraulic
Hydraulic Hose	N/A	N/A	N/A	Standard on 3-Point; 2 each 24' length optional on bucket mount	Standard
Component Protection	Shear-Pin	Shear-Pin	Shear-Pin or Radial Pin**	N/A	N/A
Max Auger RPM	94	94	94/75	109/105	97/85
Auger Length	30"	48"	48"	48"	48" (9" is 46" length)
Auger Sizes	6", 9" or 12"	6", 9" or 12"	6", 9", 12", 15", 18" or 24"	6", 9", 12", 15", 18" or 24"	9", 12", 15", 18", 24" or 36"
Flighting 6", 9", 12"	Semi-Double				
Flighting 15", 18", 24", 36"	Double				
Options	7" or 14" Auger extension Hydraulic cylinder down pressure kit (Applies approx. 500 lbs. of force) Auger alignment handle, Storage stand			Hydraulic cylinder down pressure kit on 3-point only 3-pt Storage stand 7" or 14" Auger extension	24" or 48" Auger extension

* See dealer for complete warranty information.

**Radial Pin recommended on auger sizes of 15" and above.

Models may or may not include options.

Design and specifications subject to change without notice.