

# We're up front about our rear discharge mowers. They're superb!

## FDR25 SERIES

15 - 50 HP — 72", 84"

**5** year  
Limited  
Gearbox Warranty

**Quick Hitch**

- Cat. 1 Hitch
- 3/16" Deck thickness
- Lower hitch clevises adjust in and out for greater leverage
- Floating 3-point for superior ground hugging capabilities
- Non-corrosive plated spacers to change cutting height from 1"– 5 1/2"
- Solid rubber tires on 72" model
- Semi-solid tires on 84" model
- 1" Wheel spindles with nylon bushings for smooth casting
- 3 Medium lift heat treated blades
- High blade tip speed
- 1" Machined blade spindle with ball bearings and cast iron housing
- Single B-section Kevlar belt, spring loaded for maximum performance
- Driveline storage hook



Rounded front corner without lip helps protect trees and fences.

**Rear discharge mowers** require higher horsepower, especially in tall, dense grass. For maximum performance, use in regularly maintained areas.



Blade spindles and bearings are precision fit in a cast iron housing.



Grease bearings from top without removing belt covers.

## We'll even stand behind it!

We've long been looked upon as a leader in 3-Point Grooming Mowers. Our mowers have been copied by others, but we will continue to lead through innovation and design. Our FDR25 Series Rear Discharge Mower is built tough for tough jobs and long days. Discharging grass out the rear of the mower is what people want; it leaves a clean cut, it doesn't discharge debris high in the air, it discharges grass evenly over a wide surface, and it doesn't discharge into unwanted areas. And it's a product we back with a 5 year limited gearbox warranty!

- Working widths to match most needs and tractor tire spacing.
- A 3-point hitch that floats and adjusts to fit various tractor hitch and tire combinations.
- A top link that features two settings to adjust to various tractor lift capabilities.




3/8" Gearbox support channel handles high stress loads.

Greaseable wheel bearings and spindle shaft allows for smooth rolling and turning.

Main drive cast iron pulley offers superior strength and belt slippage control in all types of mowing conditions.



Solid rubber tires on 72" model are sandwiched between the rim halves and bolted in.



Some tractor and tire combinations do not allow enough room for the mower hook-up. Longer lower hitch clevises are available to easily correct this situation.



Steel chassis — The all welded steel chassis forms a single integrated unit designed to support the mowing deck and to absorb shock loads incurred by the wheels and the front of the deck.



5/16" Front edge support protects deck

Land Pride's unique baffling system performs with results to make professionals smile. Strategically located to maximize air flow for clean distribution, yet minimize grass obstruction, our underside deck design is simple, yet very effective.