

Features and Benefits

Blades, Rear

RB25 Series

Features	Benefits
Warranty	One year parts & labor. See warranty page for complete details.
72", 84", 96" Working widths	Choice of three sizes to pick from.
25-60 HP range	Fits a wide variety of small tractors between 25 & 60 HP.
Fits Land Pride Quick-Hitch	Allows for quick and easy one person hook-up.
Blade angles left and right up to 60° in either direction	(9 Forward positions in 15° increments and 5 reverse positions in 30° increments) Many angles for diverse jobs and results.
17 1/2" High rolled moldboard	Rolls the material for less drag.
5/16" Moldboard thickness	Offers thickness for rugged work.
1/2" x 6" Heat-treated reversible cutting edge	Gives twice the life from the cutting edge by being able to reverse it.
Retractable Parking Stand	Keeps the frame off the ground and makes hook-up easier.
Landscape Rake adaptable	Remove moldboard and add rake element to add diversity of frame.
Skid shoes (optional)	Set depth of blade to clear obstructions like manhole covers, street cracks.
End plates (optional)	End plates allow blade to hold in material to move.
Gauge wheel (optional)	Set depth of blade to do level grading.

RB35 Series

Features	Benefits
Warranty	One year parts & labor.
72", 84", 96" Working widths	Choice of three sizes to pick from.
35-80 HP rating	Fits a wide variety of small tractors between 35 & 80 HP.
Cat. 1 & 2 Hitch	Fits wide variety of tractors.
Fits Land Pride Quick-Hitch	Allows for quick and easy one person hook-up.
Blade angles left and right up to 60° in either direction	(9 Forward positions in 15° increments and 5 reverse positions in 30° increments) Many angles for diverse jobs and results.
Blade offsets left or right 12"	(7 positions: Center, 3 left and 3 right) Helps extend blade past tractor tire.
Blade tilts up and down up to 30°	(5 positions: Center, 2 clockwise and 2 counterclockwise) Allows operator to do simple tasks such as putting a crown in the middle of a road to making V-type ditches.
Heavy turntable housing (dog house)	Keeps all parts fitting snug to eliminate premature wear. Extends life on threaded shaft.
17 1/2" High rolled moldboard	Rolls material for less drag.
5/16" Moldboard thickness	Offers thickness for rugged work.
2" x 2 x 3/8" Angle iron reinforcement on 84" & 96" Moldboards	Gives 84" & 96" moldboard added strength.
1/2" x 6" Heat-treated reversible cutting edge	Gives twice the life from the cutting edge by being able to reverse it.
Retractable Parking Stand	Keeps frame off ground during storage, also allows for easy hook-up.
Landscape Rake adaptable	Landscape Rake can be added.
End plates (optional)	End plates allow the blade to hold dirt in to move it.
Skid shoes (optional)	Set depth of blade to clear obstructions such as manhole covers or street cracks.
Gauge wheel (optional)	Can be used for more precise grading by keeping the moldboard at a fixed position.

Designs, specifications, features and information are subject to change without notice.