



**OS15 Series**

<b>Features</b>	<b>Benefits</b>
<b>LED Signal lights</b>	LED lights are bright, long lasting, and resistant to vibration, unlike incandescent counterparts.
<b>2" or 3" (5.4 or 7.6 cm) Spacing</b>	Knife spacing for different geographic soil types, conditions and moisture.
<b>Seed to soil contact</b>	Knives create a slit, the seed is precisely placed in the slit and the roller incorporates seed to soil contact (for better seed germination).
<b>Easy seed cup and seedbox emptying</b>	Flute is designed to allow easy clean out of material in seedbox and seed flutes.
<b>Seedbox agitator</b>	Eliminates seed bridging.
<b>Seed cups with powder metal flutes</b>	Superior metering accuracy by each flute. Powder metal dissipates heat to keep cups running cool.
<b>Gauge wheel or rear roller seed cup drive</b>	Gauge wheels keeps knives in ground more consistently in undulating terrain. Rear roller drive allows for closer seeding to obstructions.
<b>Water tight seedbox</b>	Keeps water out and seeds in.
<b>Wind guarded seed drop</b>	Seed rate is consistent across width of the machine and is not hampered by windy conditions.
<b>Straight Knives</b>	More aggressive, picks up thatch.
<b>Curved Knives</b>	Less aggressive and less disturbance of thatch layer.
<b>Small seeds box</b>	Simultaneously seeds second type of seed.
<b>Slit seeder attachment</b>	Guides seed directly into slit. Good for overseeding expensive grasses to ensure good seed to soil contact.
<b>Front roller (Option)</b>	Used to set seeding depth with units equipped with rear roller drive. Precise depth control.
<b>Working widths</b>	48", 72"
<b>Horsepower rating</b>	25-60 hp
<b>Offset hitch – 48" unit</b>	Offset by 10" to cover right tire track.
<b>Fits Land Pride Quick Hitch</b>	Aids in one person hook-up.
<b>Machine weights</b>	48" - 1260 lbs; 72" - 1605 lbs.
<b>0"-1 1/2" (0-13 mm) Depth adjustment</b>	Adjust depth for different seed types, soil conditions, and moisture.
<b>High carbon heat-treated knives</b>	Last longer in sandy soils.
<b>High tensile roller chain</b>	Provides a smooth and quiet drive.
<b>1 Bushel per foot seedbox</b>	Fill less often with a large box.
<b>Seed splash guard</b>	Seedbox lid has a guard to prevent seed from being spilled between lid and box.
<b>Heavy-duty lid</b>	Lid won't buckle or slam shut in high winds.
<b>Lift hooks</b>	Allow for easy loading and unloading from trailers
<b>Packer wheel scraper</b>	Prevents soil buildup on packer wheels in moist conditions.
<b>Covered drive chains</b>	Drive chains are covered for safety, as well as keeping tree branches away to eliminate chain jumping.
<b>Warranty</b>	5 Years on gearbox. One year parts and labor.