

FDR25 Series Rear Discharge Mowers

Features	Benefits
2 Cutting widths	72" and 84"
Gearbox HP rating	15 - 60 HP
Rear discharge	The wide, even dispersal of grass leaves a fine thin layer directly behind the mower, vs. a possible windrow to the side. Keeps grass from blowing in unwanted areas. Easier to mow around objects.
Deflectors	Built-in to throw material and debris down.
Clevis type lower hitch points	Allows for easy hook-up by being able to remove pins and back into clevises.
Floating 3-Point	Top and bottom hitch points float up and down which allows the mower to float over uneven terrain.
5/16" Rolled front on deck	5/16" roll formed front deck edging designed to take heavy abuse.
Frame-over-deck design	Frames takes stress out of deck by supporting it.
3/16" Deck thickness	Heavy deck material to aid in overall strength and longevity. Reinforced spindle mounts.
Lower hitch points adjust in and out	Accommodates many tractor configurations by adjusting in and out.
FDR2572 Only - Solid rubber tires with roller bearings	Solid rubber tires on the FDR2572 are sandwiched between the rim halves, bolted in, and can't go flat. Roller bearings allow for a long life.
FDR2584 Only - Semi solid tires with roller bearings	Semi solid tires on the FDR2584 offer premium flotation. Roller bearings allow for a long life. Semi solid tires offer shock absorption.
Heavy-duty Gauge wheel arms	1/4" Gauge wheel arms increases strength.
Non-aligned gauge wheels	Rear wheels don't track behind the front wheels to reduce laying grass over.
High blade tip speed	72" = 18,130 fpm For cleaner cutting and better dispersion of clippings. 84" = 17,210 fpm
Choices of blades	Low, medium, high-lift, or mulching blades are available to match customer needs and specific applications.
Blade overlap	Blade overlap of 1 1/4" assures no skipping in tight turns.
1 3/8" Machined blade spindle with ball bearings and cast iron housing.	Machined spindle for balanced performance and accuracy, ball bearings for smooth and quiet running, cast iron housing for added protection and durability.
Top greasing spindles	Assures top bearing gets grease. No shields to remove.
Single B-section Kevlar belt	Simple one belt design. Kevlar material adds additional strength.
Vacuum formed ABS belt guards	No scratching, no rattling.
Spring loaded adjustable idler	Allows for constant and proper tension on belt. Better than adjusting gearbox for belt tension.
Blade bar	Bar gives additional support to blade. (Not available on FDR2572)
Top Hitch	Top hitch has two hook-up points which allows greater lifting leverage for smaller tractors.
5 Year Limited Gear Box warranty	Shows our confidence in the gearbox integrity. 5 year Parts & Labor with S/N 329841+.
Driveline hanger	For ease in hookup and storage of driveline. Keeps driveline off ground.
Quick Hitch Compatible	Compatible with Land Pride Quick Hitch for easy attachment and removal increases productivity.